

COURTAULDS AEROSPACE INC -- EPOXY MIL-P23377 PRIMER GREEN LOW IR #515X370 --
8010-01-048-6539

=====
===== Product Identification =====

Product ID:EPOXY MIL-P23377 PRIMER GREEN LOW IR #515X370

MSDS Date:06/03/1992

FSC:8010

NIIN:01-048-6539

Kit Part:Y

MSDS Number: CCJZY

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:757 CALIFORNIA ST

Box:1800

City:GLENDALE

State:CA

ZIP:91203

Coun

try:US

Info Phone Num:818-549-7973

Emergency Phone Num:818-549-7973

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====
===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA 313)(CERCLA)(VP = 22.0)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 20.0%

Other REC Limits:NONE RECOMMENDE

D

OSHA PEL:100 PPM/STEL 150

ACGIH TLV:50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL N-AMYL KETONE (VP = 2.1)

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

Ingred Name:BISPHENOL A EPOXY RESIN

CAS:25036-25-3

Fraction by Wt: 20.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:STRONTIUM CHROMATE (SARA 313)(CERCLA)

CAS:7789-06-2

RTECS #:GB3240000

Fraction by Wt: 15.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:STEL 0.05 MG/M3

ACGIH TLV:0.0005 MG/M3 AS CR

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:IRON OXIDE

CAS:51274-00-1

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3 TDUST

ACGIH TLV:5 MG/M3 AS FE

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313)
(CERCLA)(VP = 74.9)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/STEL 300

ACGIH TLV:200 PPM/STEL 300

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 L

BS

Ingred Name:TALC (NON-ASBESTIFORM)

CAS:14807-96-6

RTECS #:MW2700000

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: