View NSN Online: https://aerobasegroup.com/nsn/8010-01-048-6539

COURTAULDS AEROSPACE INC -- AMINE ACTIVATOR DES LOW IR EPOXY PA ACTIVATOR 910X654

-- 8010-01-048-6539

Product ID:AMINE ACTIVATOR DES LOW IR EPOXY PA ACTIVATOR 910X654

MSDS Date:12/18/1991

FSC:8010

NIIN:01-048-6539

Kit Part:Y

MSDS Number: CCJZZ === Responsible Party ===

Company Name: COURTAULDS AEROSPACE INC

Address:757 CALIFORNIA ST

Box:1800

City:GLENDALE

State:C

Α

ZIP:91203 Country:US

Info Phone Num:818-549-7973

Emergency Phone Num:818-549-7973

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ingred Name: XYLENE)ARA 313) (CERCLA) VP 10

CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 5.0% Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM 150 STEL ACGIH TLV:100 PPM/150STEL

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: ETHYL BENZENE (SARA 313) VP 7.1

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: AIR, MAY COLLECT IN

LOW/CONFINED AREAS.USE GROUNDING/BONDING PROCEDURES WHEN TRANSFERRING. AVOID FREE-FALL LIQUID. DON'T SMOKE. KEEP FROM HOT SURFACES.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:WHERE TLV EXCEEDED OR SPRAY MIST PRESENT, US F

NIOSH/MSHA APPROVED RESPIRATOR. IN CONFINED AREA, AIR-SUPPLIED RESPIRATORS. FOLLOW RESPIRATOR MFR DIRECTION/OSHA REGULATION 29 CFR 1910.134 FOR RESPIRATOR USE.

Ventilation: GEN GILUTION/LOCAL EXHAUST TO KEEP LEVEL BELOW TLV/PEL. WHERE EMPLOYEES NOT EXPOSED KEEP LEVEL BELOW 25% OF LEL.

Protective Gloves: CHEMICAL RESISTANT GLOVES.

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING, SAFETY SHOWER, EYEBATH, WASHING FACILITIES

SHOULD BE AVAILABLE.

Supplemental Safety and Health

DO NOT ENTER AREAS W/O FOLLOWING APPROPRIATE PROCEDURES INCLUDING AIR MONITERING, USE OF SUPPLIED AIR IF NECESSARY & PRESENCE OF OBSERVER FOR ASSISTANCE. OBSERVE PRECAUTIONARY LABEL WARNINGS.

========= Physical/Chemical Properties ===========

HCC:F2

Boiling Pt:B.P. Text:180 TO 277F

Vapor Density:>AIR Spec Gravity:0.87

Evaporation Rate & Department of the Reference: SLOWER THAN BUAC Appearance and Odor: CLEAR LIQUID, SOLVENT ODOR Per

========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES NONE RECOGNIZED Stability Condition to Avoid:NONE RECOGNIZED Hazardous Decomposition Products:PRODUCTS OF COMBUSTION HAZARDOUS (CARBON MONOXIDE, CARBON DIOXIDE).
======== Disposal Considerations ============
Waste Disposal Methods:PACKAGE, STORE, TRANSPORT, MANAGE IN ACCORDA W/LOCAL, STATE, FEDERAL REGULATIONS, NO METHOD

Waste Disposal Methods:PACKAGE, STORE, TRANSPORT, MANAGE IN ACCORDANCE W/LOCAL, STATE, FEDERAL REGULATIONS. NO METHOD IS TO BE USED THAT

WOULD POSE ENVIRONMENTAL OR HUMAN HEALTH THREAT, INCLUDING ANY WHICH WOULD CONTAMINATE GROUND OR SURFACE WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shoul

cent Volatiles by Volume:84.2

d seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.