

COURTAULDS AEROSPACE, INC -- AMINE WATERBORNE PRIMER C.S. #910X831 --
8010-01-292-8894

=====
===== Product Identification =====

Product ID:AMINE WATERBORNE PRIMER C.S. #910X831

MSDS Date:03/25/1994

FSC:8010

NIIN:01-292-8894

Kit Part:Y

MSDS Number: CCKFJ

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Inf

o Phone Num:818-240-2060

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====
===== Composition/Information on Ingredients =====

Ingred Name:MODIFIED ALIPHATIC AMINE

Fraction by Wt: 20.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2-PROPOXYETHANOL (SARA 313)(

VP = 1.3)
CAS:2807-30-9
RTECS #:KM2800000
Fraction by Wt: 15.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS ADDITIVES, RESINS, PIGMENTS

Fraction by Wt: 200F,>93C

Lower Limits:1.1

Extinguishing Media:NFPA CLASS B EXTINGUISHERS, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:COOL FIRE-EXPOSED CONTAINERS W/WATER. WEAR NIOSH/MSHA APPROVED SCBA/PROTECTIVE CLOTHING TO PREVENT SKIN/EYE CONTACT.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE/EXPLODE

WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROTECT EQUIP. AVOID SKIN/EYE CONTACT/BREATHING VAPORS. SMALL: DIKE/ABSORB W/INERT MATL. USE EMERGENCY RESPONSE PERSONNEL IF MANAGING SPILL BEYOND CAPABILITY IN HOUSE PERSONNEL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DON'T TAKE INTERNALLY.

PREVENT CONTACT W/CONTAM

CLOTHES. WASH CONTAM CLOTHES BEFORE REUSE. FOLLOW LABEL WARNINGS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL OPERATING CONDITIONS.

IN AREAS WHERE TLV EXCEEDED/SPRAY MIST PRESENT USE NIOSH/MSHA APPROVED AIR-SUPPLIED RESPIRATOR. FOLLOW RESPIRATOR MFR DIRECTIONS/OSHA REGS 29 CFR 1910.134 FOR RESPIRATOR USE.

Ventilation:ADEQUATE GEN DILUTION/LOCAL EXHAUST. IF NOT EXPOSED KEEP LE

VEL BELOW 25% OF LOWER EXPLOSIVE LIMIT.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER PROTECTIVE CLOTHES. SAFETY SHOWER, EYEBATH, WASHING FACILITIES.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 340F

Vapor Density:>AIR

Spec Gravity:1.0

Evaporation Rate & Reference:SLOWER THAN BUAC

Appear

ance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:81.95

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE RECOGNIZED

Stability Condition to Avoid:FIRE OR EXCESS HEAT.

Hazardous Decomposition Products:CARBON, CARBON MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:NOT IGNITABLE HAZ WASTE ACCORDING TO FED REGS. CHECK W/STATE ENVIRO AGENCY TO SEE IF REGULATED IN ANY WAY. NO DISPOSAL METHOD. DON'T POSE ENVIROMENTAL/HUMAN HEALTH THREAT, CONTAMINATE GROUND/SURFACE W ATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should s

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.