

NILES CHEMICAL PAINT CO -- N-6488A GRAY EPOXY: PART A -- 8010-01-380-2388

=====
Product Identification
=====

Product ID:N-6488A GRAY EPOXY: PART A
MSDS Date:01/10/1996
FSC:8010
NIIN:01-380-2388
Kit Part:Y
MSDS Number: CCKMQ
=== Responsible Party ===
Company Name:NILES CHEMICAL PAINT CO
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Info Phone Num:616-683-3377
Emergency P
hone Num:219-236-5856
Preparer's Name:MIKE LICHATOWICH
CAGE:02388

==== Contractor Identification ====
Company Name:NILES CHEMICAL PAINT
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Phone:616-683-3377/219-236-5856
CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 33.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2.0 MG/M3
ACGIH TLV:2.0 MG/M3

Ingred Name:AMINE COMPOUND (VP =

1.0 @ 20C)
Fraction by Wt: 28.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL ALCOHOL (SARA 313)(CERCLA)(VP = 4.4 @ 20C)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 23.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM SKIN
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 9.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMIDO-AMINE-RESIN
CAS:68443-08-3
Fraction by Wt: 3.0%
Other REC Limits:N
ONE RECOMMENDED

Ingred Name:XYLENE (SARA 313)(CERCLA)(VP = 7.0 @ 20C)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/STEL 150
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PROPRIETARY INGREDIENT
Fraction by Wt: BALANCE
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:SEVERE IRRITATION, LACRIMATION, REDNESS, BLURRED VISION. SKIN:HARMFUL IF ABSORBED. INHAL:NASAL & RESP IRRITATION, CNS DEPRESSION (DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, CONFUSION) NAUSEA, HEADACHE, VERTIGO, UNCONSCIOUSNESS, ASPHYXIATION. INGEST:GI IRRIT, NAUSEA, ABDOMINAL PAIN, VOMITTING, DIARRHEA.

Effects of Overexposure:CHRONIC:RESPIRATORY TRACT, IRRIT CORNEAL INFLAMMATION, PHOTOPHOBIA. SEVERE SKIN & EYE IRRIT

. LIVER, KIDNEYS, CNS INCOHERENCE, CORNEAL INFLAMMATION, ANOREXIA.

Medical Cond Aggravated by Exposure:NK TARGET ORGANS:SKIN/EYES/RESP SYSTEM, LIVER, KIDNEYS, CNS, GI TRACT & BLOOD. SKIN DRYNESS MAY OCCUR, NUISANCE DUST.

===== First Aid Measures =====

First Aid:INHAL:MOVE TO FRESH AIR IMMED. IF BREATH STOPPED,GIVE ARTIF RESPIRATION. GET MED AID ASAP. SKIN:IMMED FLUSH W/ PLENTY H2O. IF MAT'L PENETRATES CLOTH,IMMED REMOVE CONTAM CLOTH & FLUSH SKIN W/WATER. GET MED AID. EYE:IMMED FLUSH W/LG AMT WATER >15 MIN, LIFT UPPER/LOWER LIDS. GET MEDICAL AID IMMED. NO CONTACTS. INGEST:DRINK 1-2 LG GLASSES WATER, DON'T INDUCE VOMIT. CALL DR/POISON CNTRL. TREAT SYMPTOMS

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:79.0F,26.1C

Autoignition Temp:Autoignition Temp Text:NE

Lower Limits:1.0

Upper Limits:15.0

Extinguishing Media:DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:

WEAR SCBA W/FULL FACEPIECE (POSITIVE PRESSURE MODE) & FULL PROTECT CLOTH. USE WATER TO COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.VAPOR HEAVY,TRAVEL ON GRND TO IGNIT.KEEP FROM HEAT/IGNIT.CLSD CNTNR EXPLODE W/HEAT.APPLIC TO HOT SRFCS REQ SPCL CAUTN.DECOMP PRODUCT-HEALTH HZD.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNIT SOURCE. MINIMIZE

VAPOR

BREATHING/AVOID SKIN CONTACT. SMALL:ABSORB W/INERT MAT'L (CLAY,SOIL,COMMERCIAL ABSORBENT). SHOVEL RECLAIMED LIQ/ABSORBENT INTO RECOVERY/SALVAGE DRUMS. LRG:DIKE. RECLAIM INTO RECOVERY/SALVAGE DRUMS OR TANK TRUCK.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. SHOCK FROM DROPPING MAY SPLIT CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROPRIATE (TYPE TC-23C-75) FITTED HALF-MASK OR FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING & AFTER APPLIC UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS BELOW APPLC LEVELS. FOLLOW RESPI RATOR MANUFACTURER'S DIRECTIONS FOR USE.

Ventilation

:KEEP AIR

Spec Gravity:1.301

pH:NA

VOC Grams/Liter:2.67

Viscosity:95-105 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, ODOR OF SOLVENTS, GREEN, GRAY

Percent Volatiles by Volume:39.56

Corrosion Rate:MINIMAL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, ACIDS. WILL SOFTEN POLYETHELENE, POLYPROPYLENE, PVC CNTNRS.

Stability Condition to Avoid:HIGH T

TEMPERATURES

Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

Conditions to Avoid Polymerization:HIGH TEMPERATURES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS. EPA D001 IGNITABLE HAZARDOUS WASTE.

=====
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.