View NSN Online: https://aerobasegroup.com/nsn/5970-01-386-6169

## VARFLEX CORPORATION -- VARGLAS SILICONE RESIN 500 -- 5970-01-386-6169

============= Product Identification ===============

Product ID: VARGLAS SILICONE RESIN 500

MSDS Date:07/23/1993

FSC:5970

NIIN:01-386-6169

MSDS Number: CCKPZ === Responsible Party ===

Company Name: VARFLEX CORPORATION

Address:512 WEST COURT STREET

City:ROME State:NY ZIP:13440 Country:US

Info Phone Num:315-336-4400

Emergency Phone Num:315-336-4400

CAGE:79074

=== Contractor Identification ===

Company Name: VARFLEX CORPORATION

Address:512 WEST COURT STREET

Box:City:ROME

State:NY ZIP:13440 Country:US

Phone:315-336-4400

CAGE:79074

======= Composition/Information on Ingredients ========

Ingred Name:FIBROUS GLASS

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST

Ingred Name: SILICONE COATING--METHYL, PHENYL

Other REC Limits: NONE RECOMMENDED

======= Hazards Identification ========

========

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. ACUTE- THE FIBERS FROM THIS PRODUCT ARE MECHANICAL IRRITANTS AND MAY CAUSE TRANSITORY IRRITATION TO EXPOSED AREAS SUCH AS EYES, SKIN AND UPPER RESPIRATORY TRACTS. ORAL:UNLIKELY TO OCCUR. CHRONIC- NONE.

Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION

**Medical Cond** 

Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS OR EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. DO NOT RUB OR SCRATCH IRRITATED AREAS. INHALED:REMOVE TO FRESH AIR. PROV IDE OXYGEN/CPR IF NEEDED. O RAL:UNLIKELYTO OCCUR.

=========== Fire Fighting Measures =============

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL. Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

========= Accidental Release Measures ================

Spill Release Procedures:WEAR APPROVED RESPIRATOR AND CHEMICALLY COMPATIBLE GLOVES IF NEEDED. FOR DUST AND FIBERS GENE RATED DURING

FABRICATION, VACUUM OR SWEEP UP. AVOID CREATING DUST. PLACE IN APPROPRIATE CONTAINER FOR WASTE DISPOSAL. VENTILATE AREA AND WASH SPILL SITE.

Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE AWAY FROM DIRECT SUNLIGHT, AT A RELATIVE HUMIDITY OF 30-60%. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:AVOID INHALATION OF FIBERS. AVOID CONTACT WITH EYES AND SKIN. WASH THOROUG

====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE NORMALLY REQUIRED. IN DUSTY SITUATION, A NIOSH APPROVED AIR SUPPLIED RESPIRATOR OR DUST RESPIRATOR IS ADVISED.
Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE AT THE MINIMUM.
Protective Gloves:LEATHER OR COTTON
Eye Protection: GOGGLES/SAFETY GLASSES
Other Protective Equipment:EYE WASH STATION, EMERGENCY SHOWER
Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.
Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:N1
NRC/State Lic Num:NOT RELEVANT
Spec Gravity:2.54
Viscosity:NOT RELEVANT
Evaporation Rate & Dr. Reference: NOT RELEVANT
Solubility in Water:NOT RELEVANT
Appearance and Odor:SILICONE RESIN COATED WITH NO ODOR
======== Stabil
ity and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES NONE
Hazardous Decomposition Products:BINDERS MAY PRODUCE CARBON MONOXIDE, CARBON DIOXIDE AND OTHER HYDROCARBONS.
======= Disposal Considerations ===========
Waste Disposal Methods:DISPOSE IN MUNICIPAL OR INDUSTRIAL LANDFILL. COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulate

HLY AFTER HANDLING MATERIAL.

d for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.