View NSN Online: https://aerobasegroup.com/nsn/8030-00-080-1549

Product ID:PR 1440 B-1/2,1440 B 2, BASE COMPOUND MSDS Date:11/06/1995 FSC:8030 NIIN:00-080-1549 Kit Part:Y MSDS Number: CCLMZ === Responsible Party === Company Name: COURTAULDS AEROSPACE INC Address:5430 SAN FERNANDO ROAD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info P hone Num:818-549-7586/240-2060 Emergency Phone Num:800-228-5635/800-424-9300(CHEMTREC) CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 93C Extinguishing Media:WATER FOG, CAR BON DIOXIDE, SAND, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. Fire Fighting Procedures: DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Spill Release Procedures: USE PROTECTIVE EQUIPMENT. SCOOP SPILL INTO CONTAINER FOR DISPOSAL. WASH SPILL AREA WITH A SUITABLE SOLVENT AFTER PICK UP IS CO MPLETE. Neutralizing Agent:NOT RELEVANT Handling and Storage Precautions: STORE IN CLOSED CONTAINERS. KEEP OUT OF REACH OF CHILDREN. Other Precautions: DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. LAUNDER BEFORE REUSE. Respiratory Protection:NONE REQ UIRED. Ventilation: GENERAL VENTILATION Protective Gloves: NEOPRENE, RUBBER, LATEX Eye Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: SAFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE LOCATED NEARBY. Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health KEY1:N1. THIS PRODUCT IS A KIT CONSISTING OF TWO PARTS: ACCELERATOR AND BASE COMPOUND. 

==== HCC:N1

NRC/State Lic Num:NOT RELEVANT Boiling Pt:=110.C, 230.F B.P. Text:230F - 350F Vapor Density:>1 Spec Gravity:1.571 VOC Pounds/Gallon:35 Evaporation Rate & amp; Reference: