View NSN Online: https://aerobasegroup.com/nsn/7930-00-992-7411

RADIATOR SPECIALTY COMPANY -- S-C SUPER CONCENTRATE DEGREASER, PN:SC-(ALL SIZES) -- 7930-00-992-7411

Product ID:S-C SUPER CONCENTRATE DEGREASER, PN:SC-(ALL SIZES) MSDS Date:11/01/1994 FSC:7930 NIIN:00-992-7411 MSDS Number: CCLVG === Responsible Party === Company Name: RADIATOR SPECIALTY COMPANY Address:1400 W. INDEPENDENCE BLVD. City:CHARLOTTE State:NC ZIP:28208 Country:US Info Phone Num:704-377-6555 Emergency Phone Num:704-377-6555 Preparer's Name:K. PHILLIPS-CHEMIST CAGE:77628 === Contractor Identification === Company Name: RADIATOR SPECIALTY CO Address:600 RADIATOR RD Box:159 **City:INDIAN TRAIL** State:NC ZIP:28079-0159 Country:US Phone:704-377-6555 CAGE:26965 Company Name: RADIATOR SPECIALTY COMPANY Address:1900 WILKINSON BLVD. Box:34689 City:CHARLOTTE State:NC ZIP:28208 Country:US Phone:704-377-6555/303-623-5716 CAGE:77628

======= Composition/In

formation on Ingredients =========

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE CAS:68476-34-6 Fraction by Wt: 54-56% Other REC Limits:NONE RECOMMENDED

Ingred Name:ALIPHATIC PETROLEUM OIL CAS:64742-06-9 Fraction by Wt: 29-30% Other REC Limits:NONE RECOMMENDED

Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 2-3% Other REC Limits:NONE RECOMMENDED OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9596

Ingred Name:PETROSUL 2729; (SODIUM PETROLEUM SULFONATE) CAS:68608-26-4 RTE CS #:WR7150000 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:NONYLPHENOL POLYETHOXATE CAS:9016-45-9 RTECS #:MD0900000 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:TLV:100PPM(AIR)ALIPHATIC PETRO DISTILLAT Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE:MODERATE IRRIT. SKIN:IRRIT .PROL

EXPO MAY CAUSE DERM & DEFATTING. INHAL:LUNG IRRIT ON PROL EXPO. INGEST:HARMFUL OR FATAL IF SWALLOWED. NAUSEA,VOMITING & LUNG DAMAGE IF ASPIRATED.

Effects of Overexposure:MODERATE EYE IRRIT, SKIN IRRIT, DERMATITIS, DEFATTING. LUNG IRRIT. INGEST HARMFUL OR FATAL. NAUSEA, VOMITING, LUNG DAMAGE IF ASPIRATED.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE:FLUSH W/WAER FO

| R | @LEASAT 15MINS THOROUGHLY WHILE LIFTING |
|---|---|
| | EYELIDS.CONSULT PHYSICIAN IF ADVERSE EFFECTS PERSIST. SKIN:WASH |
| | W/SOAP/WATER THOROUGHLY.REMOVE CONTAMIN CLOTH. INHAL:MOVE TO FRESH |
| | AIR IMME D.IF ADVERSE EFFECTS PERSIST CONSULT PHYSICIAN. INGEST:DO |
| | NOT INDUCE VOMIT.DO NTO ADMINISTER ADRENALIN OR EPINEPHRINE.GET MED |
| | HELP IMMED. |

Flash Point Method:TCC Flash Point:159F,71C Autoignition Temp:Autoignition Temp Text:NP L ower Limits:NP Upper Limits:NP Extinguishing Media: FOAM, CO2, DRY CHEMICAL. CAUTION! COMBUSTIBLE!! Fire Fighting Procedures:WEAR SELF-CONTAINED, POSITIVE PRESSURE BREATHING APPARATUS & PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:NONE KNOWN. CAUTION! COMBUSTIBLE!! Spill Release Procedures: OBSERVING HEALTH HAZARDS DESCRIBED IN MSDS VENTILATE AREA, REMOVE IGN SOURCES. CONFINE SPILL. WIPE UP W/RAGS & TRANSFER TO WASTE DRUM. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: STORE IN COOL PLACE BELOW 120F AWAY FROM IGNITION SOURCES & OXIDZING AGENTS. Other Precautions: WEARING CONTACT LENSES IS INADVISABLE. KEEP AWAY FROM CHILDREN AND ANIMALS. Respiratory Protection: CONSUMER: NA. BULK HNDLG: IF TLV IS EXCEEDED WEAR NIOSH APPO RVED RESP. Ventilation: CONSUMER: USE W/ADEQUATE VENTILATION. BULK HNDLG: GENERAL. Protective Gloves: BULK HNDLG: NEOPRENE GLOVES. Eye Protection: CONSUMER: NA. BULK HNDLG: GOGGLES. Other Protective Equipment: CONSUMER: NA. BULK HNDLG: NEOPRENE GLOVES, APRON. Work Hygienic Practices: LAUNDER CONTAMIN CLOTHING BEFORE REUSE. Supplemental Safety and Health

HCC:V4 Boiling Pt:B.P. Text:>300F,>149C Melt/Freeze Pt:M.P/F.P Text:N/DETERMINE De comp Temp:Decomp Text:NP Vapor Pres:N/DETERMIN Vapor Density:N/DETERMIN Spec Gravity:0.83-0.86 pH:9-10 Viscosity:NP Evaporation Rate & amp; Reference:N/DETERMINED. Solubility in Water:EMULSIFIES Appearance and Odor:DARK AMBER LIQUID WITH PETROLEUM ODOR. Percent Volatiles by Volume:>80 Corrosion Rate:NP

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER

Hazardous Decomposition Products: FIRE: NORMAL PRODUCTS OF COMBUSTION; CARBON DIOXIDE, CARBON MONOXIDE & ACRID SMOKE.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE GOVERNMENT LAWS & REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.