View NSN Online: https://aerobasegroup.com/nsn/6350-01-261-9862

CHEMTRONICS INC -- ULTRAJET 2000 SYSTEM REFILL ES520/ES1020/ES1020K/ES1020R 6350-01-261-9862

Product ID:ULTRAJET 2000 SYSTEM REFILL ES520/ES1020/ES1020K/ES1020R MSDS Date:07/13/1994 FSC:6350 NIIN:01-261-9862 MSDS Number: CCLZC === Responsible Party === **Company Name: CHEMTRONICS INC** Address:8125 COBB CENTER DRIVE City:KENNESAW State:GA ZIP:30144 Country:US Info Phone Num:800-645-5244 Emergency Phone Num:800-424-9300 CHEMTREC Preparer's Name: MICHAEL S. WATKINS CAGE:2M589 === Contractor Identification === Company Name: CHEMTRONICS INC (CANCELLED USE 21267) City:HAUPPAUGE State:NY ZIP:11760 Country:US CAGE:2M589 **Company Name: SIGNALTONE INC** Address:946 FRISBIE ST. Box:City:CADILLAC State:MI ZIP:49601 Country:US Phone:616-775-1373 CAGE:64189 Company Name: SUPPLY DEPOT INC Address:2830 VIA ORANGE WAY **Box:UNKNOW** City:SPRING VALLEY State:CA ZIP:91978 Country:US

Phone:619-660-2813/FAX 800-236-5519 CAGE:04ZR5

Ingred Name:TETRAFLUOROETHANE CAS:811-97-2 Fraction by Wt: 100% Other REC Limits:100 PPM AEL-DUPONT

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: HARMFUL IF I NHALED; MAY CAUSE ASPHYXIATION. CONTACT WITH LIQUID MAY CAUSE FROSTBITE, IRRITATION. INGESTION MAY CAUSE FROSTBITE OF MOUTH & THROAT TISSUES. CHRONIC: NONE SPECIFIED BY MANUFACTURER . Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure:INHALED-DIZZINESS, UNCONSCIOUSNESS, DEATH. SKIN-IRRITATION, FROSTBITE. EYES-IRRITATION, FROSTBITE. INGESTED-FROSTBITE OF MOUTH & THROA T.

Medical Cond Aggravated by Exposure:PRE-EXISTING MEDICAL CONDITONS OF THE HEART, LUNG, SKIN, EYE.

First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-TREAT FOR FROSTBITE THEN FLUSH WITH WATER FOR 15 MINUTES. SKIN-REMOVE CONTAMINATED CLOTHES. TREAT FOR FROSTBITE THEN WASH WITH MILD SOAP & WATER. INHALED-REMOV E TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. INGESTED-TREAT FRO FROSTBI TE & OBTAIN

IMMEDIATE MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM WHEN EXTINGUISHING FIRES INVOLVING THIS MATERIAL. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explos

ion Hazard:NONE SPECIFIED BY MANUFACTURER.

Spill Release Procedures:SHUT OFF LEAK IF POSSIBLE & SAFE TO DO SO. WEAR SELF-CONTAINED BREATHING APPARATUS & APPROPRIATE PERSONAL PROTECTIVE GEAR. ABSORB SPILL WITH INERT MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. DO NOT FLUSH TO SEWER. KEEP OUT OF WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=============

Handling and Storage Precautions: STORE IN A COOL, DRY PLACE AWAY FROM HEAT & OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE IN DIRECT SUNLIGHT.

Other Precautions: KEEP OUT OF REACH OF CHILDREN. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN, EYES, CLOTHING. WASH HANDS BEFORE EATING. USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR OR MIST.

Respiratory Protection: IF ENGINEE

RING CONTROLS FAIL OR NON-ROUTINE USE

OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation: USE GOOD GENERAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: RUBBER OR CHEMICALLY RESISTANT GLOVES.

Eye Protection: SAFETY GLASSES W/FACESHIELD.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING,

OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS IS FOR REFILL CYLINDER FOR SIGNALTONE-NEIMAN PART NUMBER 65800 "BIG HORN".

HCC:V2 Boiling Pt:B.P. Text:-16F,-27C Vapor Pres:4241 Vapor Density:3.18 Spec Gravity:1.21 Evaporation Rate & amp; Reference:>1 (N-BUTYL ACETATE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR, COLORLESS GAS; SLIGHT ETHEREAL ODOR. Percent Volatile Stability Indicator/Materials to Avoid:YES

DO NOT MIX WITH POWDERED ALKALI & ALKALINE EARTH METALS OR STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT SPRAY NEAR OPEN FLAMES, RED HOT SURFACES, OR OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products: THERMAL DECOMPOSITION MAY RELEASE HYDROFLUORIC ACID VAPOR.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

====== D

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS. WATER RUNOFF CAN CAUSE ENVIRONMENTAL DAMAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all li

ability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.