View NSN Online: https://aerobasegroup.com/nsn/9150-01-439-1875

MIL-COMM PRODUCTS CO, INC -- MC-2500, "TW-25B OIL" -- 9150-01-439-1875

Product ID:MC-2500, "TW-25B OIL" MSDS Date:11/24/1998 FSC:9150 NIIN:01-439-1875 MSDS Number: CCMFL === Responsible Party === Company Name: MIL-COMM PRODUCTS CO, INC Box:43278 City:UPPER MONTCLAIR State:NJ ZIP:07043 Country:US Info Phone Num:201-743-5404/ FAX 201-743-7139 **Emergency Phone Num:20** 1-743-7139 CAGE:0BAN7 === Contractor Identification === Company Name: MIL-COMM PRODUCTS COMPANY, INC Address:2 CARLTON AVE Box:City:EAST RUTHERFORD State:NJ ZIP:07073 Country:US Phone:201-935-8561 Contract Num:SP0450-00-M-C002 CAGE:0BAN7

Ingred Name:CALCIUM SULFONATE Other REC Limits:NONE RECOMMENDED

Ingred Name:TRICRESYLPHOSPHATE CAS:1330-78-5 RTECS #:TD0175000 Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC SULFONATE Ot her REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE OR SKIN IRRITATION. INHAL: LOW TO MEDIUM.REMOVE TO FRESH AIR.EYE:IRRITANT.WASH FREQUENTYLY W/WATER.SKIN:IRRITANT.WASH FREQUENTLY W/SOAP/WATER.INGEST:LOW TO MEDIUM.USE GOOD HYGIENIC PRACTICE. Е xplanation of Carcinogenicity:PER MSDS:CHEM LISTED AS CARCINOGE OR POTENTIAL CARCINOGE:NTP/IARC/OSHA:NO. Effects of Overexposure: EYE/SKIN IRRIT. Medical Cond Aggravated by Exposure:NONE KNOWN. First Aid:WASH SKIN W/SOAP/WATER.WASH EYES W/WATER FOR 15MINS.DO NOT INDUCE VOMITING.DRINK WATER & SEE PHYSICIAN. Flash Point Method:COC Flash Point:=237.8C,

460.F Autoignition Temp:Autoignition Temp Text:UNK Extinguishing Media:FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS. WATER MAY CAUSE FROAMING TO OCCUR. Unusual Fire/Explosion Hazard:NONE.

Spill Release Procedures:DIKE & USE ABSORBENT TO CONTAIN SPILL.PLACE IN CNTNR & RECOVER OR INCINERATE.DO NOT ALLOW TO FLOW INTO SEWERS OR WATERWAYS. Neutralizing Agent:NONE SPECIFIED BY MAN UFACTURER.

Handling and Storage Precautions:USE CAUTION TO LIMIT EXPOSURE TO EYES/SKIN.DO NTO BREATHE MIST. Other Precautions:NONE SPECIFIED BY MANUFACTURER.

Respiratory Protection:MIST. Ventilation:LOCAL EXHAUST RECOMMENDED. MECHANICAL (GENERAL) RECOMMENDED. Protective Gloves:RUBBER GLOVES. Eye Protection:GOGGLES. Other Protective Equipment:PROTECTI

## VE CLOTHING SUGGESTED. Work Hygienic Practices:USE GOOD HYGIENIC PRACTICES. Supplemental Safety and Health

HCC:V6 Boiling Pt:=337.8C, 640.F Melt/Freeze Pt:=-65.C, -85.F Decomp Temp:Decomp Text:NP Vapor Pres:NA Vapor Density:NA Spec Gravity:1.1 pH:NP Viscosity:NP Evaporation Rate & amp; Reference:NP Solubility in Water:1%, SLIGHT. Appearance and Odor:SWEET ODOR, PALE YELLOW COLOR. Percent Volatiles by Volume:NP Corrosion Rate:N P

Stability Indicator/Materials to Avoid:YES STRONG ACIDS & BASES & OXIDIZING AGENTS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE TOXIC.

Waste Disposal Methods:RECOVER OR INCINERATE.DO NOT ALLOW TO FLOW INTO SEWERS OR WATERWAYS. OBEY LOCAL, STATE AND FEDERAL REGULATIONS.

Discl

aimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.