View NSN Online: https://aerobasegroup.com/nsn/8030-00-247-2525

FEL-PRO CHEMICAL PRODUCTS LP -- GS-3 GASKET SEALER 51071,51072 -- 8030-00-247-2525

Product ID:GS-3 GASKET SEALER 51071,51072 MSDS Date:03/16/1995 FSC:8030 NIIN:00-247-2525 MSDS Number: CCMPV === Responsible Party === Company Name: FEL-PRO CHEMICAL PRODUCTS LP Address:3412 W TOUCHY AVE City:CHICAGO State:IL ZIP:60645 Country:US Info Phone Num:847-568-2377 Emergenc y Phone Num:847-568-2377 Preparer's Name: CATHY GRIFFITH CAGE:GO402 === Contractor Identification === Company Name: FEL-PRO CHEMICAL PRODUCTS DIV OF FELT PRODUCTS Address:7450 N MCCORMICK Box:1205 City:SKOKIE State:IL ZIP:60076-8205 Country:US Phone:303-289-5651 CAGE:GO402 Company Name: FEL-PRO CHEMICAL PRODUCTS LP Address:3412 WEST TOUHY AVE Box:City:LINCOLNWOOD State:IL ZIP:60645 Country:US Phone:303-289-5651 CAGE:05VH4

Ingred

Name:ISOPROPYL ALCOHOL (SARA 313)(LD50 ORAL RAT 5045 MG/KG) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 30.0% Other REC Limits:MFR REC TLV 400 PPM OSHA PEL:400 PPM ACGIH TLV:400 PPM/STEL 500

Ingred Name:1-METHOXY-2-PROPANOL (LD50 ORAL RAT 5660 MG/KG) CAS:107-98-2 RTECS #:UB7700000 Fraction by Wt: 5.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 MG/M3 ACGIH TLV:100 MG/M3/STEL 150

Routes of Entry: Inhalation:YES Skin:YE

S Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYE: SEVERE IRRIT. SKIN: MILD IRRITANT. CHRONIC CONTACT MAY CAUSE DEFATTING/REDNESS. INHAL: BREATHING LIQ PARTICLES MAY INJURE LUNGS/LIVER/KIDNEYS. VAPOR MAY HAVE STRONG OFFENSIVE ODOR CAUSING HEADACHE/NAUSEA/VOMITING. CAUSES RESP TRACT IRRIT. INGEST: MAY BE HARMFUL/FATAL. MAY CAUSE NAUSEA/VOMITING.

Medical Cond Aggravated by Exposure:PREEXISTING PULMINARY & DERMA

TOLOGICAL DISORDERS W/EXPOSURE TO HAZARDOUS COMPONENTS.

First Aid:EYES: IMMEDIATELY FLUSH W/PLENTY OF WATER >15 MINUTES. GET MEDICAL AID. SKIN: REMOVE CONTAM CLOTHES. WASH W/SOAP & WATER. GET MEDICAL AID. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIF RE SP. IF TROUBLE BREATHING GIVE OXYGEN. GET MED AID. INGESTION: DON'T INDUCE VOMITING. GIVE GLASS WATER/MILK. CALL DR/POISON CONTROL IMMED. NEVE

R GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Flash Point Method:TCC Flash Point:45.0F,7.2C Lower Limits:2.5 Upper Limits:12.0 Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM. Fire Fighting Procedures:NIOSH APPROVED SCBA/FULL PROTECTIVE CLOTHES. USE WATER TO COOL EXPOSED CNTNRS. WATER STREAM DIRECTED AT FIRE MAY CAUSE FROTHING W/SPREAD OF FLAME. Unusual Fire/Explosion Hazard:CLSD CNTNRS EXPOSED TO HIGH HE AT MAY

RUPTURE/EXPLODE. VAPORS >AIR. MAY TRAVEL ALONG GROUND/REIGNITE AT DISTANT SOURCE/FLASHBACK.

Spill Release Procedures:REMOVE IGNITION SOURCES. DIKE/CONTAIN SPILL. WEAR APPROPRIATE PROTECTIVE EQUIPMENT. ABSORB W/INERT MATERIAL (CLAY). SWEEP/SHOVEL INTO LOOSELY COVERED WASTE CONTAINER. REMOVE TO APPROPRIATE WASTE AREA.

Handling and St

orage Precautions:STORE CNTNRS AWAY FROM HEAT/SPARKS/FLAME/OTHER IGNIT SOURCES. USE W/ADEQUATE VENTILATION. FOLLOW ALL LABEL PRECAUTIONS EVEN IF CNTNR EMPTY. Other Precautions:CONTAINER MAY RETAIN RESIDUE. GROUND/BOND CONTAINER WHEN TRANSFERRING MATERIAL. AVOID CONTACT W/EYES, SKIN, CLOTHES. FOR INDUSTRIAL USE ONLY. KEEP CLOSED WHEN NOT IN USE. KEEP AWAY FROM CHILDREN.

Respiratory Protection:IF TLV/PEL EXCE EDED, USED IN POORLY VENTILATED SPACE, OR IF INHALATION EFFECTS OCCUR, USE NIOSH APPROVED VAPOR CARTRIDGE RESPIRATOR ACCORDING TO APPLICABLE HEALTH/SAFETY REGULATIONS & MANUFACTURER REC OMMENDATIONS. Ventilation:LOCAL EXHAUST NEEDED TO CONTROL VAPOR OR DUST LEVELS TO BELOW LOWEST COMPONENT TLV. Protective Gloves:BUTYL RUBBER, NITRILE, PVA GLOVES Eye Protection:CHEMICAL SPLASH GOGGLES Other Protective Equipment:ACCESSIBLE EYEWASH & SAFETY SHOWER. CLEAN CLOTHES TO COVER SKIN. W ork Hygienic Practices:GEN INDUSTRIAL SAFETY PRECAUTIONS. DON'T

ork Hygienic Practices:GEN INDUSTRIAL SAFETY PRECAUTIONS. DON'T SMOKE/EAT DURING USE.DON'T REUSE EMPTY CNTNRS W/O COMMERCIAL CLEAN/RECONDITION. Supplemental Safety and Health NK

HCC:F2 Boiling Pt:B.P. Text:180 TO 206F Melt/Freeze Pt:M.P/F.P Text: