

THETFORD CORPORATION -- AQUA KEM -- 4510-00-339-2930

=====  
Product Identification  
=====

Product ID:AQUA KEM

MSDS Date:05/31/1996

FSC:4510

NIIN:00-339-2930

MSDS Number: CCMQK

=== Responsible Party ===

Company Name:THETFORD CORPORATION

Address:7101 JACKSON RD

City:ANN ARBOR

State:MI

ZIP:48103

Country:US

Info Phone Num:313-769-6000

Emergency Phone Num:313-769-6000(CHEMTREC 800-424-9300)

CAGE:DO910

=

== Contractor Identification ==

Company Name:THETFORD CORP

Address:7101 JACKSON ROAD

Box:City:ANN ARBOR

State:MI

ZIP:48106

Phone:(734) 769-6000

CAGE:61431

Company Name:THETFORD CORPORATION

Address:7101 JACKSON ROAD

City:ANN ARBOR

State:MI

ZIP:48103

Country:US

Phone:734-769-6000

CAGE:DO910

=====  
Composition/Information on Ingredients  
=====

Ingred Name:FORMALDEHYDE (SARA 302/313) (CERCLA)

CAS:50-00-0

RTECS #:LP8925000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE 1910.1048

AC

GIH TLV:C 0.3 PPM, A2; 9596

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingrid Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 200 PPM

ACGIH TLV:S,200PPM/250STEL; 96

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES

IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: CAN PRODUCE EYE DAMAGE & SKIN SENSITIZATION. HIGH INHALATION EXPOSURE MAY CAUSE BRONCHOPNEUMONIA, RESPIRATORY IRRITATION. CHRONIC: NOT MUTAGENIC, NOT TERATOGENIC. PROLONGED/REPEATED EXPOSURE TO VAPORS MAY CAUSE CANCER, CONTAINS FORMALDEHYDE-A KNOWN CARCINOGEN.

Explanation of Carcinogenicity:CONTAINS F [50-00-0] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALA

TION-RESPIRATORY IRRITATION, NAUSEA, WEAKNESS, HEADACHE. EYE-DAMAGE, SEVERE IRRITATION, BURNS. SKIN-SENSITIZATION, DISCOMFORT, RASH. POSSIBLE CARCINOGEN.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING DISEASES OF LUNGS, SKIN, EYES MAY HAVE INCREASED SUSCEPTIBILITY TO HAZARDS OF OVEREXPOSURE.

=====  
===== First Aid Measures =====

First Aid:FLUSH AREA WITH LARGE AMOUNTS OF WATER. IRRIGATE EYES FOR A MINIMUM OF 15 MINUTES. IF SWALL

OWED, INDUCE VOMITING BY GIVING 2

GLASSES OF WATER & STICKING FINGER DOWN THROAT. FOR EYE CONTACT OR INGESTION, CALL PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:137F,58C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM FOR USE ON ALCOHOL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE.

=====  
===== Accidental Release Measures =====

=====

Spill Release Procedures:VENTILATE AREA. WEAR PROPER PERSONAL PROTECTIVE GEAR TO INCLUDE RESPIRATORY PROTECTION. CLEAN UP SMALL SPILLS WITH WATER. ABSORB WITH INERT MATERIAL. NEUTRALIZE REMAINDER WITH AMMONIA/WATER MIXTURE. M OP AREA WITH PLENTY OF WATER.  
Neutralizing Agent:WATER-AMMONIA MIXTURE.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 110F. DO NOT FREEZE.  
Other Precautions:DO NOT GET LIQUID IN EYES OR ON SKIN. DO NOT INHALE VAPORS. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.  
Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).  
Protective Gloves:RUBBER, P VC, NEOPRENE.  
Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.  
Other Protective Equipment:PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION & SAFETY SHOWER.  
Work Hygienic Practices:AVOID UNECESSARY AND PROLONGED EXPOSURE. AVOID BREATHING VAPORS.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:210F,99C  
Vapor Pres:17-20  
Vapor Density:1.03  
Spec Gravity:1.08  
pH:3.5-5  
Evaporation Rate & Ref

erence:>1 (N-BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:BLUE LIQUID WITH PUNGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PHENOLS, STRONG MINERAL ACIDS, STRONG OXIDIZING AGENTS, STRONG ALKALIS.

Stability Condition to Avoid:ELEVATED TEMPRTATURES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE  
CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OC  
CUR.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION OR BIOLOGICAL TREATMENT IN  
STATE/FEDERAL APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any per

son utilizing this

document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.