

PDI INC -- PLASTIDIP -- 5970-01-038-0593

===== Product Identification =====

Product ID:PLASTIDIP

MSDS Date:06/01/1997

FSC:5970

NIIN:01-038-0593

MSDS Number: CCMSH

=== Responsible Party ===

Company Name:PDI INC

Address:3760 FLOWERFIELD RD

City:MINNEAPOLIS

State:MN

ZIP:55434

Country:US

Info Phone Num:612-785-2156

Emergency Phone Num:800-424-9300(CHEMTREC)

Preparer's Name:NOT GIVEN

CAGE:0B629

=== Co

ntractor Identification ===

Company Name:KAMPI COMPONENTS CO., INC.

Address:210 RT 13

Box:721

City:BRISTOL

State:PA

ZIP:19007-3517

Country:US

Phone:215-736-2000

CAGE:7Z016

Company Name:P D I INC

Address:3760 FLOWEFIELD RD

Box:City:CIRCLE PINES

State:MN

ZIP:55014

Country:US

Phone:612-785-2156

CAGE:55638

Company Name:PDI INC

Address:3760 FLOWERFIELD RD

Box:City:CIRCLE PINES

State:MN

ZIP:55014-3919

Country:US

Phone:612-785-2156

CAGE:0B629

Company Name:PIONEER VALVE AND FITTING CO INC

Address:93 SEI

GAL ST  
Box:City:BROOKLYN  
State:NY  
ZIP:11206-3204  
Country:US  
Phone:718-387-4724  
CAGE:66200

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM & P NAPHTHA  
CAS:8030-30-6  
RTECS #:DE3030000  
Fraction by Wt: 37.0%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HEXANE (N-HEXANE) (CERCLA)  
CAS:110-54-3  
RTECS #:MN9275000  
Fraction by Wt: 18.5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:500 PPM  
ACGIH TLV:50 PPM; 9596  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (S  
ARA 313) (CERCLA)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 14.8%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM; Z-2  
ACGIH TLV:S, 50 PPM; 9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 3.7%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM/300STEL;9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:RESINS  
Fraction by Wt: 26%  
Other REC Limits:N

ONE RECOMMENDED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF

OVEREXPOSURE. BRAIN AND NERVOUS SYSTEM DAMAGE (REFERRED TO AS SOLVENTS OR PAINTERS SYNDROME). DRYING OR CRACKING SKIN.

Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NO. CONTAINS

TOLUENE-CHEM KNOWN TO STATE OF CA TO CAUSE BIRTH DEFECTS/OTHER REPRODUCTIVE HARM.

Effects of Overexposure:HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, IRREGULAR HEARTBEAT, SKIN/EYE IRRIT.

Medical Cond Aggravated by Exposure:PRE-EXISTING HEART, LIVER, KIDNEY, AND LUNG DISORDERS. TARGET

ORGANS:CNS, CVS, PNS, LIVER, KIDNEY, LUNGS, RESPIRATORY SYSTEM, SKIN.

=====  
===== First Aid Measures =====

First Aid:INGEST:CONTACT PHYSICIAN OR POISON CONTROL IMMEDIATE.

INHAL:REMOVE TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY. EYE:FLUSH W/LG AMTS OF WATER. IF IRRIT PERSISTS CONTACT PHYSICIAN . SKIN:WASH W/SOAP/WATER.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: