View NSN Online: https://aerobasegroup.com/nsn/9150-01-411-9132

Product ID:TRANE OIL 15 MSDS Date:04/13/1993 FSC:9150 NIIN:01-411-9132 MSDS Number: CCQWF === Responsible Party === Company Name: TRANE/SERVICE FIRST Address:4500 MORRIS FIELD DR City:CHARLOTTE State:NC ZIP:28208 Country:US Info Phone Num:704-398-4600 Emergency Phone Num:704-398-4600 CAGE:6X583 === Contracto r Identification === Company Name: TRANE/SERVICE FIRST Address:4500 MORRIS FIELD DR Box:City:CHARLOTTE State:NC ZIP:28208 Country:US Phone:704-398-4600 CAGE:6X583 Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (SEVERE)

HEAVY NAPHTHENIC; (REFINED MINERAL OIL) CAS:64742-52-5 RTECS #:PY8035001 OSHA PEL:5MG/M3 OIL MIST(MFR) ACGIH TLV:N/K

LD50

LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PROLONGED CONTACT MAY CAUSE MINOR SKIN IRRITATION. Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTF RESP) . EYES:FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF REDNESS OR IRRITATION PERSISTS, CONTACT MD. SKIN:WASH W/SOAP & WATER. WASH CLOTHING BEFORE REUSE. INGEST:CALL MD.
======================================
Flash Point Method:COC Flash Point:>300F,>149C Extinguishing Media:USE WATER FOG, DRY CHEM, CARBON DIOXIDE, FOAM OR SAND/EARTH TO EXTING FIRE. WATER SPRAY IS UNSUITABLE AS EXTING AGENT
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . Unusual Fire/Explosion Hazard:NONE.
======================================
Spill Release Procedures:STOP LEAK & DIKE UP LARGE SPILLS. USE INERT ABSORBENT MATERIAL SUCH AS EARTH, SAND OR VERMICULITE FOR CLEAN-UP. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:STORE IN A COO L, DRY PLACE. AVOID EXPOSURE TO HEAT & FLAME. PROTECT AGAINST EYE & SKIN CONTACT. Other Precautions:NONE SPECIFIED BY MANUFACTURER.
======================================
Respiratory Protection:NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . Protective Gloves:OIL RESISTANT RUBBER GLOVES. Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS . Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . WEAR RU

BBER APRON. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health VP:500F,>260C Vapor Pres:SUPP DATA Vapor Density:>10 Spec Gravity:0.89 Evaporation Rate & amp; Reference:NEGLIGIBLE Solubility in Water:INSOLUBLE Appearance and Odor:CLEAR AMBER, VISCOUS LIQUID; PETROLEUM ODOR. Percent Volatiles by Volume:NEGLIG

Stability Indicator/Materials to Avoid:YES KEEP AWAY FROM STRONG OXIDIZING AGENTS SUCH AS CHROMIC ACID, HYDROGEN PEROXIDE & BROMINE. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:UPON COMBUSTION CO*2 & CO ARE GENERATED.

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL, STATE & LOCAL GOVERNMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of De

fense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.