View NSN Online: https://aerobasegroup.com/nsn/1680-01-229-2416

Product ID:HALON 1301 MSDS Date:11/01/1995 FSC:1680 NIIN:01-229-2416 MSDS Number: CCVMJ === Responsible Party === Company Name: PACIFIC SCIENTIFIC Address:1800 HIGHLAND AVE **City:DUARTE** State:CA ZIP:91010 Country:US Info Phone Num:818-359-9317 Emergency Phone Num:818-359-9317 CAGE:05167 === Contractor Identifica tion === Company Name: PACIFIC SCIENTIFIC CO HTL/KIN-TECH DIVISION Address:1800 HIGHLAND AVE Box:City:DUARTE State:CA ZIP:91010 Country:US Phone:818-359-9317/602-796-1100 CAGE:05167

Ingred Name:METHANE, BROMOTRIFLUORO-; (BROMOTRIFLUOROMETHANE) (HALON 1301) (SARA 313) (CERCLA) CAS:75-63-8 RTECS #:PA5425000 OSHA PEL:1000 PPM ACGIH TLV:1000 PPM Ozone Depleting Chemical:1

Ingred Name:SUPDAT:SIGNS & SYMPS OF EXPOS:ANESTH EFT

OF HALON 1301 & GLC-13B1 AT LEVELS 10% (15-20%) MAY LEAD TO (ING 4) RTECS #:9999999ZZ Ingred Name: ING 3: UNCONSCIOUSNESS & POSSIBLY DEATH. RTECS #:9999992Z LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: APPROX LETHAL CONC OF HALON 1301 & GLC-13B1 TO RAT IS >800,000 PPM FOR 15 MINS. ACUTE INHAL LC50 W/RATS IS >800,000 PPM FOR 4 HRS. HALON 1031 & GLC-13B1 HAS ANESTH & CARDIAC EFTS IN HUMANS AT CONCS >1 0% BY VOL, CONCS 10,000 PPM AS RECOMMENDED BY NIOSH. CONSULT ANSI STANDARD & OSHA REGULATIONS CONCERNING USE OF RESPIRATORY EQUIPMENT. AOVID PROLONGED EXPOSURE TO EXCESSIVE CONCENTRATIONS. Ventilation:LOC EXHST:MATL TRANSFER & HNDLG SHOULD BE CONDUCTED W/EXHAUST SYSTEM. MECH: ALL INDOOR AREAS SHOULD BE WELL VENTILATED. Protective Gloves:LINED NEOPREN E OR LEATHER GLOVES. Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS . Other Protective Equipment: EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . Work Hygienic Practices: DO NOT WEAR CONTACT LENSES. Supplemental Safety and Health EXPLO HAZ: ABOVE 1000F, HALON 1301 & GLC-13B1 MAY RELS HYDROGEN FLUORIDE, HYDROGEN BROMIDE, CARBONYL FLUORIDE & CARBONYL BROMIDE. MATLS TO AVOID: MAY DEGRADE CERTAIN POLYMERIC MATLS. HAZ DECOMP PROD:BRO MIDE. SMOKING CAN CAUSE FORM OF TH **ESE CHEMS & MUST BE** AVOIDED IN AREA OF RELS. EFTS OF OVEREXP:LENSES MAY OCCUR. (ING 2)

HCC:G3 Boiling Pt:B.P. Text:-72F,-58C Melt/Freeze Pt:M.P/F.P Text:-270F,-168C Vapor Pres:6200 @ 0C Vapor Density:5.1 Spec Gravity:1.57 (H*2O=1) Solubility in Water:0.03% BY WT Appearance and Odor:COLORLESS GAS; ODORLESS.

Stability Indicator/Materials to Avoid:YES ACTI

 VE METALS, FIRES OF METAL HYDRIDES & MATL CNTNG OWN OXYG. PROD WILL NOT EXTING FIRES OF THESE MATLS. PROD (SUPDAT)
Stability Condition to Avoid:NONE.
Hazardous Decomposition Products:IN PRESENCE OF FLAMES/HOT SURFS; HYDROGEN FLUORIDE, HYDROGEN BROMIDE, BROMINE, CARBONYL FLUORIDE & CARBONYL (SUPP DATA)

Waste Disposal Methods:RETURN CYLINDERS TO GREAT LAKES CHEMICAL CORPORATION, EL DORADO, ARKANSAS.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.