

HAARTZ-MASON -- N-700-A NEOPRENE MAINTENANCE COATING BLACK -- 8030-00-145-0111

===== Product Identification =====

Product ID:N-700-A NEOPRENE MAINTENANCE COATING BLACK

MSDS Date:04/30/1992

FSC:8030

NIIN:00-145-0111

MSDS Number: CCXNB

=== Responsible Party ===

Company Name:HAARTZ-MASON

Address:370 PLEASANT STREET

City:WATERTOWN

State:MA

ZIP:02172

Country:US

Info Phone Num:617-926-2300

Emergency Ph

one Num:617-926-2300/800-OIL-TANK (SPILL)

CAGE:KO262

=== Contractor Identification ===

Company Name:HAARTZ-MASON

Address:370 PLEASANT STREET

City:WATERTOWN

State:MA

ZIP:02172

Country:US

Phone:617-926-2300

CAGE:KO262

Company Name:HAARTZ-MASON, INC.

Address:270 PLEASANT STREET

Box:322

City:WATERTOWN

State:MA

ZIP:02172

Country:US

Phone:617-926-2300

CAGE:84697

===== Composition/Information on Ingredients =====

Ingred Name:RUBBER

Other REC Limits:NONE RECOMMENDED

Ingred Name:CARB

ON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYCHLOROPRENE SYNTHETIC  
Other REC Limits:NONE SPECIFIED

Ingred Name:ALUMINUM SILICATE  
CAS:1332-58-7  
RTECS #:GF1670500  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:VOLATILE ORGANIC SUBSTANCES: 5.40 #/GAL/0.645 KG/LTR  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Sk  
in:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: NAUSEA/NARCOSIS. CHRONIC: NOT  
AVAILABLE AT PRESENT TIME. TARGET ORGANS: BASED ON ANIMAL DATA MAY  
CAUSE LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN. IN HUMANS LIVER  
ABNORMALITIES. BASED ON ANIMAL DATA MAY CAUSE ANEMIA, LIVER  
ABNORMALITIES, KIDNEY, EYE  
Effects of Overexposure:IRRITATION TO EYES AND MUCOUS MEMBRANES. CAN  
ALSO CAUSE SKIN DRYNESS. LIQUID INGESTION MAY  
RESULT IN VOMITING.  
Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS.

=====  
===== First Aid Measures =====

First Aid:UTILIZE THE SUGGESTED METHODS BELOW. IN EMERGENCY SITUATIONS  
NOTIFY PHYSICIAN IMMEDIATELY. SKIN: WAS WITH SOAP AND WATER. GET  
MEDICAL ATTENTION. EYES: FLUSH EYES ABUNDENTLY WITH CLEAN WATER AND  
REFER TO PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. GET FRESH  
AIR. GIVE OXYGEN. USE CPR IF NOT BREATHING. REFER TO DR.

=====

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:40.0F,4.4C

Autoignition Temp:Autoignition Temp Text:947F

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:CO2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:NIOSH/MSHA SCBA SHOULD BE WORN AS WELL AS PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL FIRE EXPOSED STRUCTURES AND DISPERSE VAPOR CLOUD IF FIRE IS NOT PRESENT.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND TRAVEL CO

NSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL IN SAND, EARTH, VERMICULITE, OIL-DRI, OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN APPROVED SOLVENT STORAGE AREA, KEEP TIGHTLY CLOSED. KEEP AWAY FROM HEAT, OPEN FLAMES, SPARKS,

HOT SURFACES AND OXIDIZING AGENTS.

Other Precautions:NA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED ATMOSPHERE SUPPLYING OR AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS AS REQUIRED TO MAINTAIN EXPOSURE LEVELS BELOW RECOMMENDED LIMITS.

Ventilation:LOCAL EXHAUST: REMOVE VAPORS DURING PROCESSING. MECHAN EXHAUST: EXPLOS-PROOF EQUIP. SPECIAL: REDUCE VAPOR CONC BELOW TLV

Protective Gloves:PVA GLOVES.

Eye Protection:SAFETY G LASSES.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices:KEEP AREA CLEAN. CLEAN UP SPILLS IMMEDIATLEY. PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:231F,111C

Vapor Pres:25

Vapor Density:3.2

Spec Gravity:1.028

Appearance and Odor:GREY. CHARACTERISTIC SOLVENT ODOR.

Percent Volatiles by Volume:5.4

===== Stab

ility and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NK

Stability Condition to Avoid: AVOID HEAT, OPEN FLAMES, SPARKS, HOT SURFACES, AND OXIDIZING AGENTS.

Hazardous Decomposition Products: OXIDES OF CARBON. HYDROGEN CHLORIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL CHEMICAL AND SOLVENT WASTE DISPOSAL REGULATIONS.

=====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.