View NSN Online: https://aerobasegroup.com/nsn/8030-00-297-6677

Product ID:CS 3100 PART B MSDS Date:02/05/1996 FSC:8030 NIIN:00-297-6677 Kit Part:Y MSDS Number: CCXNX === Responsible Party === Company Name: FLAMEMASTER CORP Address:11120 SHERMAN WAY City:SUN VALLEY State:CA ZIP:91352 Country:US Info Phone Num:800-424-9300 CHEMTREC Emergency Phone Num:818-982-1650 Preparer 's Name: HERBERT MOORE CAGE:14439 === Contractor Identification === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY Box:City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Phone:818-982-1650 CAGE:14439

Ingred Name:LEAD DIOXIDE CAS:1309-60-0 RTECS #:OG0700000 Fraction by Wt: 64.0% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3

Ingred Name:LEAD OXIDE CAS:1317-36-8 RTECS #:OG175 0000 Fraction by Wt: 6.0% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: WEAKNESS, STUPOR. CHRONIC: KIDNEY DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS. Effects of Overexposure: HEADACHE, MUSCLE AND JOINT PAIN, NEUROMUSCULAR DYSFUNCTION. Medical Cond Aggra vated by Exposure: ANEMIA, KIDNEY DISEASE, PREGNANCY. First Aid:INGESTION: INDUCE VOMITING, CONSULT A PHYSICIAN AT ONCE. EYE CONTACT: FLUSH WITH LARGE AMOUNT OF WATER AND CONTACT PHYSICIAN. Flash Point Method:TCC Flash Point:>200F,>93C Autoignition Temp: Autoignition Temp Text: NA Lower Limits:NA **Upper Limits:NA** Extinguishing Media: FOAM, DRY CHEMICAL, CO2 . WATER. Fire Fighting Procedures: USE A SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE, IN CONFINED AREAS. Unusual Fire/Explosion Hazard: FIRE HAZARD EXISTS IF CONTACT WITH OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS. Spill Release Procedures: SCOOP UP AND TRANSFER TO A SAFETY CONTAINER.

Handling and Storage Precautions: STORE IN COOL DRY A

REA. KEEP CONTAINERS CLOSED.

Respiratory Protection: IF SOOT IS FORMED, USE NIOSH APPROVED **RESPIRATOR.** Ventilation:LOCAL EXHAUST: AIR HOOD; MECHANICAL: FAN. Protective Gloves: RUBBER GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment: APPROPRIATE TO AVOID PROLONGED CONTACT. Work Hygienic Practices: WASH HAND BEFORE EATING, DRINKING OR SMOKING. TRAIN PERSONNEL IN THE SAFE HANDLING OF THIS PRODUCT. Supplem ental Safety and Health THE LEAD DIOXIDE COMPONENT IS LESS THAN 1-OZ WHICH IS BELOW THE AMOUNT THAT HAS TO BE REPORTED. HCC:F4 Boiling Pt:B.P. Text:644F,340C Melt/Freeze Pt:M.P/F.P Text:LIQ@RM TEMP Vapor Pres:NIL Vapor Density:NA Spec Gravity:3.00 (WATER=1) VOC Pounds/Gallon:1 pH:6.8 Viscosity:NA Evaporation Rate & amp; Reference:NIL Solubility in Water:NEGLIGIBLE Appearance and Odor: BROWN PASTE; OILY ODOR Percent Volatile s by Volume:3.0 **Corrosion Rate:NA**

Stability Indicator/Materials to Avoid:YES OXIDIZABLE MATERIALS. Stability Condition to Avoid:HIGH HEAT. Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGANICS.

Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT WITH BASE AND DISPOSE ACCORDING TO FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitabi lity of this information to their particular situation.