

FIRST BRAND CORP -- STP OIL TREATMENT, STP1015 -- 9150-01-092-3529

=====
Product Identification
=====

Product ID:STP OIL TREATMENT, STP1015

MSDS Date:01/24/1996

FSC:9150

NIIN:01-092-3529

MSDS Number: CDFZW

=== Responsible Party ===

Company Name:FIRST BRAND CORP

Address:83 WOOSTER HEIGHTS RD, BLDG 301

Box:1911

City:DANBURY

State:CT

ZIP:06813-1911

Country:US

Info Phone Num:203-731-2300, 803-554-420

8

Emergency Phone Num:203-731-2300, CHEMTREC 800-424-9300

Preparer's Name:J. O. FUNDERBURK

CAGE:0CXZ7

=== Contractor Identification ===

Company Name:PRESTONE PRODUCTS CORP

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06810-5109

Country:US

Phone:203-731-3686/830-7865

CAGE:0CXZ7

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD),
HEAVY PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Fraction by W

t: 65-80%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL, HYDROTREATED (MILD), HEAVY NAPHTHENIC
DISTILLATE, PETROLEUM

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 20-35%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PHOSPHORODITHOIC ACID, O-O-D1 C1-14-ALKYL ESTERS, ZINC
SALTS (2:1) (ZDDP)

CAS:68649-42-3

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

Ingred Name:CALCIUM SULFONATE

CAS:71486-79-8

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

Ingred Name:A

MINE GRAFTED ETHYLENE/PROPYLENE COPOLYMER

Fraction by Wt: 3-10%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ORAL-SWALLOWING LARGE AMOUNTS MAY
CAUSE GASTROINTESTINAL DISTURBANCES. EYE-MAY CAUSE EYE IRRITATION.
SKIN-MAY CAUSE IRRITATION. INHALATI

ON-EXCESSIVE INHALATION OF VAPOR

OR MIST MAY CAUSE IRRITATION OF THE NOSE AND THROAT AND CENTRAL
NERVOUS SYSTEM EFFECTS.

Explanation of Carcinogenicity:NONE OF THE COMPONENTS OF THIS PRODUCT
IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN BY IARC, NTP OR
OSHA.

Effects of Overexposure:ORAL-ABDOMINAL DISCOMFORT, BELCHING, NUASEA &
DIARRHEA. EYE-REDDENING AND SWELLING OF THE CONJUNCTIVA.
SKIN-LOCALIZED REDNESS AND SWELLING. INHALATION-HEADACHE, NAUSEA
AND DROWSINESS,

DIZZINESS.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PREEXISTING SKIN DISEASE MAY BE AT INCREASED RISK FROM EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:SWALLOWING-GET MEDICAL ATTENTION BY CALLING A PHYSICIAN, POISON CONTROL CENTER OR HOSPITAL EMERGENCY ROOM. SKIN-REMOVE CONTAMINATED CLOTHING. WASH ALL AFFECTED & EXPOSED AREAS WITH SOAP & WATER. SEEK MEDICAL ATTENTION. INHALATION-REMOVE TOFRSH AIR. IF B REATHING IS DIFFICUL, ADMINISTER OXYGEN. GIVE CPR IF NOT BREATHING. SEEK AID. EYES-FLUSH WITH COPIOUS AMOUNTS OF WATER FOR 15 MIN. SEEK AID.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:400F,204C
Extinguishing Media:USE WATER SPRAY, FOAM, CARBON DIOXIDE OR DRY CHEMICAL.
Fire Fighting Procedures:UE SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO COOL FIR E-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:THE VAPOR SPACE IN CLOSED CONTAINER MAY CONTAIN HYDROGEN SULFIDE IN EXPLOSIVE CONCENTRATIONS. HYDROGEN SULFIDE MAY BE RELEASED WHEN HEATED.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOR. COLLECT MATERIAL WITH SUITABLE ABSORBENT MATERIAL AND SHOVEL INTO APPROPRIATE CONTAINER FOR DISPOSAL. PREVEN T PRODU CT FROM ENTERING SEWER OR WATERWAYS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXPOSURE TO HIGH TEMPERATURES FOR PROLONGED PERIODS. AVOID WATER CONTAMINATION. KEEP CONTAINER CLOSED.
Other Precautions:AVOID CONTACT WITH EYES, SKIN, CLOTHING. AVOID BREATHING VAPOR AND MISTS. USE ONLY WITH ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protectio

n =====

Respiratory Protection:NONE NEEDED UNDER NORMAL USE CONDITIONS. FOR OPERATIONS WHERE THE TLV MAY BE EXCEEDED, A NIOSH/MSHS APPROVED SUPPLIER AIR RESPIRATOR IS RECOMMENDED. FOR FIREFIGHTING, USE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:GENERAL VENTILATION SHOULD BE ADEQUATE FOR NORMAL USE. IF TLV IS EXCEEDED, MECHANICAL VENTILATION SUCH AS LOCAL EXHAUST.

Protective Gloves:IMPERVIOUS GLOVES SUCH AS NITRILE.

Eye Protection:SAFETY GLASSES, CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING IF NEEDED TO AVOID PROLONGED/REPEATED SKIN CONTACT.

Work Hygienic Practices:SUITABLE WASHING AND EYE FLUSHING FACILITIES SHOULD BE AVAILABLE IN THE WORK AREA.

Supplemental Safety and Health

CONTAMINATED CLOTHING SHOULD BE REMOVED AND LAUNDERED OR DRY-CLEANED BEFORE RE-USE.U.S. DOT NON-BULK: NONE.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: