

FIRST BRAND CORP -- STP OIL TREATMENT, STP1015 -- 9150-01-092-3529

=====
Product Identification
=====

Product ID:STP OIL TREATMENT, STP1015

MSDS Date:01/24/1996

FSC:9150

NIIN:01-092-3529

MSDS Number: CDFZW

=== Responsible Party ===

Company Name:FIRST BRAND CORP

Address:83 WOOSTER HEIGHTS RD, BLDG 301

Box:1911

City:DANBURY

State:CT

ZIP:06813-1911

Country:US

Info Phone Num:203-731-2300, 803-554-420

8

Emergency Phone Num:203-731-2300, CHEMTREC 800-424-9300

Preparer's Name:J. O. FUNDERBURK

CAGE:0CXZ7

=== Contractor Identification ===

Company Name:PRESTONE PRODUCTS CORP

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06810-5109

Country:US

Phone:203-731-3686/830-7865

CAGE:0CXZ7

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD),
HEAVY PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Fraction by W

t: 65-80%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL, HYDROTREATED (MILD), HEAVY NAPHTHENIC
DISTILLATE, PETROLEUM

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 20-35%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PHOSPHORODITHOIC ACID, O-O-D1 C1-14-ALKYL ESTERS, ZINC
SALTS (2:1) (ZDDP)

CAS:68649-42-3

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

Ingred Name:CALCIUM SULFONATE

CAS:71486-79-8

Fraction by Wt: 1-3%

Other REC Limits:NONE RECOMMENDED

Ingred Name:A

MINE GRAFTED ETHYLENE/PROPYLENE COPOLYMER

Fraction by Wt: 3-10%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ORAL-SWALLOWING LARGE AMOUNTS MAY
CAUSE GASTROINTESTINAL DISTURBANCES. EYE-MAY CAUSE EYE IRRITATION.
SKIN-MAY CAUSE IRRITATION. INHALATI

ON-EXCESSIVE INHALATION OF VAPOR

OR MIST MAY CAUSE IRRITATION OF THE NOSE AND THROAT AND CENTRAL
NERVOUS SYSTEM EFFECTS.

Explanation of Carcinogenicity:NONE OF THE COMPONENTS OF THIS PRODUCT
IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN BY IARC, NTP OR
OSHA.

Effects of Overexposure:ORAL-ABDOMINAL DISCOMFORT, BELCHING, NUASEA &
DIARRHEA. EYE-REDDENING AND SWELLING OF THE CONJUNCTIVA.
SKIN-LOCALIZED REDNESS AND SWELLING. INHALATION-HEADACHE, NAUSEA
AND DROWSINESS,

DIZZINESS.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PREEXISTING SKIN DISEASE MAY BE AT INCREASED RISK FROM EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:SWALLOWING-GET MEDICAL ATTENTION BY CALLING A PHYSICIAN, POISON CONTROL CENTER OR HOSPITAL EMERGENCY ROOM. SKIN-REMOVE CONTAMINATED CLOTHING. WASH ALL AFFECTED & EXPOSED AREAS WITH SOAP & WATER. SEEK MEDICAL ATTENTION. INHALATION-REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. GIVE CPR IF NOT BREATHING. SEEK AID. EYES-FLUSH WITH COPIOUS AMOUNTS OF WATER FOR 15 MIN. SEEK AID.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Extinguishing Media:USE WATER SPRAY, FOAM, CARBON DIOXIDE OR DRY CHEMICAL.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO COOL FIRE

EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:THE VAPOR SPACE IN CLOSED CONTAINER MAY CONTAIN HYDROGEN SULFIDE IN EXPLOSIVE CONCENTRATIONS. HYDROGEN SULFIDE MAY BE RELEASED WHEN HEATED.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOR. COLLECT MATERIAL WITH SUITABLE ABSORBENT MATERIAL AND SHOVEL INTO APPROPRIATE CONTAINER FOR DISPOSAL. PREVENT

PRODUCT FROM ENTERING SEWER OR WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXPOSURE TO HIGH TEMPERATURES FOR PROLONGED PERIODS. AVOID WATER CONTAMINATION. KEEP CONTAINER CLOSED.

Other Precautions:AVOID CONTACT WITH EYES, SKIN, CLOTHING. AVOID BREATHING VAPOR AND MISTS. USE ONLY WITH ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

n =====

Respiratory Protection:NONE NEEDED UNDER NORMAL USE CONDITIONS. FOR OPERATIONS WHERE THE TLV MAY BE EXCEEDED, A NIOSH/MSHS APPROVED SUPPLIER AIR RESPIRATOR IS RECOMMENDED. FOR FIREFIGHTING, USE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:GENERAL VENTILATION SHOULD BE ADEQUATE FOR NORMAL USE. IF TLV IS EXCEEDED, MECHANICAL VENTILATION SUCH AS LOCAL EXHAUST.

Protective Gloves:IMPERVIOUS GLOVES SUCH AS NITRILE.

Eye Protection:SAFETY GLASSES, CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING IF NEEDED TO AVOID PROLONGED/REPEATED SKIN CONTACT.

Work Hygienic Practices:SUITABLE WASHING AND EYE FLUSHING FACILITIES SHOULD BE AVAILABLE IN THE WORK AREA.

Supplemental Safety and Health

CONTAMINATED CLOTHING SHOULD BE REMOVED AND LAUNDERED OR DRY-CLEANED BEFORE RE-USE.U.S. DOT NON-BULK: NONE.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: