

ACCUMETRIC INC. -- SILICONE ELASTOMER, PART A -- 8040-00-833-9563

=====
Product Identification
=====

Product ID:SILICONE ELASTOMER, PART A

MSDS Date:05/11/1995

FSC:8040

NIIN:00-833-9563

Kit Part:Y

MSDS Number: CDGHB

=== Responsible Party ===

Company Name:ACCUMETRIC INC.

Address:350 RING ROAD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385

Emergency Phone Num:5

02-769-3385

CAGE:58149

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

=====
Composition/Information on Ingredients
=====

Ingred Name:SILANE, METHYLTRIACETOXY-

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT ESTABLISHED.

ACGIH TLV:NOT ESTABLISHED.

Ingred Name:ETHYLTRIACETOXYSILANE

CAS:17689-77-9

Fraction by

Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES-IRRITATES. SKIN-IRRITATION.
INHALATION-IRRITATES EYES, NOSE AND THROAT. INGESTION-SWALLOWIN
G
LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.
Explanation of Carcinogenicity:FORMALDEHYDE IS A POTENTIAL CANCER
HAZARD AND KNOWN SKIN AND RESPIRATORY SENSITIZER.
Effects of Overexposure:EYE-REDNESS AND SWELLING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.
SKIN-WIPE OFF AND FLUSH WITH WATER. GET MEDICAL ATTENTION IF
IRRITATION DEVELOPS. INHALATION-REMOVE TO FRESH AIR. ORAL-NO FIRST
AID SHOULD BE NEEDED. COMMENTS: NONE.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:212F,100C
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING SHOULD BE WORN IF FIGHTING FIRES INVOLVING
CHEMICALS.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT AND CONTAIN FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 90F. KEEP CONTAINER CLOSED UNTIL READY TO USE.

Other Precautions:PRODUCT FORMS ACETIC ACID WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL HOAC EXPOSURE WITHIN 10 PPM OR USE RESPIRATORY PROTECTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV & PEL GUIDELINES.

Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): RECOMMENDED.

Protective Gloves:NONE SPECIFIED BY MANUFACTURER.

Eye Protection:PROPER EYE PROTECTION.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING AND SHOES AS SOON AS POSSIBLE & CLEAN THOROUGHLY BEFORE REUSE.

Supplemental Safety and Health

KEY1:N1. KIT CONTAINS A 1 OZ PRIMER IN A PLASTIC OR GLASS BOTTLE AND 4.7 OZ ADHESIVE IN A 5 OZ SIZE TUBE.

===== Physical/Chemical Properties =====

Vapor Pres: