

CAAP CO INC -- B-274 BLACK POLYURETHANE RAIN EROSION COATING -- 8010-00-459-1756
===== Product Identification =====

Product ID:B-274 BLACK POLYURETHANE RAIN EROSION COATING

MSDS Date:01/01/1995

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: CDGZN

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0

375

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:CHRISTINE L. SLEDGE

CAGE:6P753

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPES FARM ROAD

Box:City:MILFORD

State:CT

ZIP:06460

Phone:(203) 877-0375

CAGE:6P753

===== Composition/Information on Ingredients =====

Ingred Name:XYLENE (SARA 313)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 44.15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/STEL 150 PPM

ACGIH TLV:100 PPM/STEL 150 PPM

EPA

Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLISOBUTYLKETONE (MIBK) (SARA 313)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 15.98%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 0.05%
Other REC Limits:NONE SPECIFIED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

Ingred Name:RESIDUAL METHYLENE BIS (4-CYCLOHEXYLISOCYANATE)
CAS:5124-30-1

RTECS #:NQ9250000
Fraction by Wt: 0-0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.01 PPM CEILING
ACGIH TLV:0.005 PPM TWA

Ingred Name:ISOCYANATE TERMINATED POLYESTER PREPOLYMER
CAS:54954-83-5
Fraction by Wt: 39.82%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES,

IRRITATE SKIN, & CAUSE RESPIRATORY IRRITATION UPON INHALATION.

CHRONIC: REPEAT/ PROLONG EXPOSURE MAY CAUSE DEFATTING OF THE SKIN, DERMATITIS, AND POSSIBLE SENSITIZATION . INHALATION OF VERY HIGH VAPOR CONCENTRATIONS OR PROLONGED EXPOSURE MAY CAUSE NEURAL DYSFUNCTION, KIDNEY & LIVER DAMAGE

Effects of Overexposure:VAPOR EXPOSURE: BURNING EYES, HEADACHE, DIZZINESS, THROAT IRRITATION, LOSS OF APPETITE, NAUSEA. CONTACT: MAY CAUSE IRRITATION OF SKIN, BURNING OF SKIN OR EYES.

Me

dical Cond Aggravated by Exposure:PREEXISTING ALLERGIES, EYE, SKIN AND RESPIRATORY DISORDERS.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WTR, GET IMMEDIATE MED ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN PROMPTLY W/ SOAP & WATER. IF SIGNS & SYMPTOMS OF EXPOSURE EXIST, GET IMMEDIATE MED ATTENTION. INHALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY, GET IMMEDIATE MED ATTENTION. INGESTION: DON'T INDUCE VOMITING. GET IMMEDIATE MED AID. IF

VOMITING

SPONTANEOUSLY KEEP HEAD BELOW HIPS TO PREVENT BREATHING VOMITUS INTO LUNGS.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:68.0F,20.0C

Lower Limits:1.0

Upper Limits:8.0

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:USUAL METHODS FOR FLAMMABLE LIQUID. NOT MISCIBLE WITH WATER-USE WATER TO COOL FIRE EXPOSED CONTAINERS. WEAR SCBA ALONG WITH PROTECTIVE CLOTHING, SOLVENT RESISTANT COATS/BOOTS/GLOVES/HELMET

Unusual Fire/Explosion

Hazard:NONE, PRODUCT IS A FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES-DON'T SMOKE IN AREA. WEAR PROTECTIVE EQUIPMENT WITH SOLVENT RESISTANT GLOVES/APRON/BOOTS/SCBA IN POSITIVE PRESSURE DEMAND MODE/POSITIVE PRESSURE AIR-SUPPLIED RESPIRATOR. DIKE & SOAK UP WITH ABSORBENT. CLEANUP WITH ABSORBENT/CONTAIN. SWEEP/WET MOP WITH SOAP & WATER. VENT AREA.

===== Handling and Storage =====

Handling and Storage Precautions

ions:FOR MORE COMPLETE HEALTH/SAFETY INFO
ON USE OF COATINGS CONTAINING RESIDUAL ISOCYANATE PLEASE CONSULT
MOBAYS HEALTH AND SAFETY INFORMATION BROCHURE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPOR/MIST, WEAR NIOSH RESP FOR EMISSION
LEVELS AT POINT OF USE. RESP W/FULL FACEPIECE/PURIFY CARTRIDGE RESP
FOR ORGANIC VAPOR/MIST, SCBA IN PRESS DEMAND MODE/POSITIVE PRESS
AIR-SUPPLD RESP. SPRAY APPLIC, SPRAY BOOTH

Ventilation:E

XHST VENT TO KEEP CONC BELOW PEL. VENT AIR PAST OPRATR,
VAPOR SRC, THEN EXHST. FOLLOW GUIDELINES-"INDUSTRIAL VENT".

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SAFETY GOGGLES. DO NOT WEAR CONTACT LENS

Other Protective Equipment:SOLVENT RESISTANT APRON AND BOOTS FOR
SPILLS.

Work Hygienic Practices:EYEWASH/SAFETY SHOWER SHOULD BE NEARBY/READY TO
USE. WASH WELL WITH SOAP AND WATER AFTER HANDLING THE PRODUCT.

Supplemental Safety and Health
KIT CONSISTS OF EIGHT PARTS.

===

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:241-281F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:8.0

Vapor Density:3.6

Spec Gravity:(H2O=1): 0.96

pH:6.0

Evaporation Rate & Reference:(BUTYL ACETATE=1): 0.85

Solubility in Water:INSOLUBLE

Appearance and Odor:BLACK AROMATIC LIQUID (COATING SOLUTION).

Percent Volatiles by Volume:60.13

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OX

IDENTIFYING AGENTS.

Stability Condition to Avoid: ALL IGNITION SOURCES, HOT SURFACES, AND TEMPERATURES ABOVE 100F (38C).

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, AS WELL AS TRACES OF HCN MAY BE RELEASED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE; RCRA HAZARDOUS IGNIT WASTE. DISPOSE ACCORDING TO STATE/LOCAL/FEDERAL REG. WHEN THE B-274, CURING AGENT, ACCELERANT OR ARE MIXED TOGETHER & THE SOLVENT IS ALLOWED TO EVAPORATE, THE SOLID END PRODUCT IS A NON-HAZARDOUS LANDFILL ITEM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.