

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3204 TYPE II CLASS A, PART A --
8030-00-889-3531

=====
Product Identification
=====

Product ID:CS 3204 TYPE II CLASS A, PART A

MSDS Date:01/01/1996

FSC:8030

NIIN:00-889-3531

Kit Part:Y

MSDS Number: CDHCM

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Pho

ne Num:818-892-1650

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:HERBERT MOORE

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM

A

CGIH TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LIQUID POLYSULFIDE POLYMER
CAS:68611-50-7
Fraction by Wt: 55.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC = 140 G/L
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE EYE, SKIN AND NOSE
IRRITATION. MAY LEAD TO MUSCULAR WEAKNESS AND DIZZINESS. LONG TERM
EXPOSURE MAY LEAD TO DERMATITIS, LIVER AND KIDNEY DAMAGE.
Effects of Overexposure:EYE, NOSE, OR SKIN IRRITATION. HEADACHE AND
NAUSEA WITH IMPAIRED COORDINATION.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS,
RESPIRATORY TRACT, LIVER OR KIDNEY DISEASE.

===== First Aid Measures =====

First Aid:EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS
WATER. CALL DR. SKIN: WASH
WITH MILD SOAP & WATER.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:90.0F,32.2C
Lower Limits:1.3
Upper Limits:7.1
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER.
Fire Fighting Procedures:IN CONFINED AREAS SELF-CONTAINED BREATHING
APPARATUS SHOULD BE WORN.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND CAN
TRAVEL TO SOURCE OF IGNITION.

===== Accidental Release =====

ease Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCE. TRANSFER TO SAFETY CONTAINER. CLEAN UP REMAINDER W/AROMATIC NAPHTHA/SAND/SWEEPING COMPOUND. WASH AREA W/SOAP & WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL WELL-VENTILATED AREA. GROUND CONTAINERS WHEN FILLING OR EMPTYING.

Other Precautions:WASH HANDS BEFORE EATING DRINKING OR SMOKING, AFTER HANDLING THIS PRODUCT.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR VAPORS ABOVE 200 PPM NEED SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST: HOOD. MECHANICAL (GENERAL): FAN.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES, FACE SHIELD.

Other Protective Equipment:APPROPRIATE TO PREVENT PROLONGED CONTACT WITH SKIN.

Work Hygienic Practices:TRAIN PERSONNEL IN SAFE HANDLING OF THIS PRODUCT.

Supplemental Safety and Health

NK

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:231F,111C

Melt/Freeze Pt:M.P/F.P Text: