

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- PRIMER COATING:
EPOXYCHEMICAL/SOLVENT RES 724400 -- 8010-00-142-9279

=====
Product Identification
=====

Product ID:PRIMER COATING: EPOXYCHEMICAL/SOLVENT RES 724400

MSDS Date:03/03/1995

FSC:8010

NIIN:00-142-9279

Kit Part:Y

MSDS Number: CDJNY

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHIT

A

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SOLVENT) (SARA III) (CERCLA) (VAPOR PRESSURE 22 MM
HG @ 20C) (LFL 1.7; UFL 7.1) (SKIN)

CAS:108-8

8-3

RTECS #:XS5250000

Fraction by Wt: 20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:50 PPM; 147 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:DIGLYCIDYL ETHER OF BISPHENOL -A RESIN (RESIN)

CAS:25068-38-6

RTECS #:KC2100000

Fraction by Wt: 20%

Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SOLVENT) (SARA 313) (CERCLA) (VAPOR PRESSURE 5 MM
HG @ 20C) (LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SOLVENT) (SARA 313) (CERCLA)
(VAPOR PRESSURE 16 MM HG @ 20C) (LFL 1.0; UFL 8.0)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM; STEL 75 PPM

ACGIH TLV:50 PPM; STEL 75 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL BENZENE (SOLVENT) (SARA 313) (VAPOR PRESSURE 1 MM HG

@ 20C) (LFL 1.0; UFL 6.7) (SKIN)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 115F) AND SOURCES
OF IGNITION.

Hazardous Decomposition Products:BURNING,INCLUDING WHEN HEATED BY
WELDING OR CUTTING,WILL PRODUCE SMOKE,CARBON MONOXIDE,CARBON
DIOXIDE,OXIDES OF CHROMIUM

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE &
LOCAL LAWS/REGULATIONS. CONTAINS CHROMIUM. RESIDUE MAY BE HAZARDOUS
WASTE (40

CFR 261.74-). DISCARDED DIRECTLY WOULD BE CLASSIFIED
HAZARDOUS WASTE. RCRA CLASSIFICATION: D001.

=====
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person

utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.