

COURTAULDS -- POLYTHIOETHER POLYMER COMPOUND PR-1826, A-1, PART B --  
8030-01-329-9998

=====  
===== Product Identification =====

Product ID:POLYTHIOETHER POLYMER COMPOUND PR-1826, A-1, PART B

MSDS Date:10/21/1993

FSC:8030

NIIN:01-329-9998

Kit Part:Y

MSDS Number: CDJTP

=== Responsible Party ===

Company Name:COURTAULDS

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info

Phone Num:818-240-2060

Emergency Phone Num:800-228-5635/ 818-240-2060

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====  
===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (SARA III)(VP = 70.0)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10.0%

Other REC Limits:NONE SPEC

IFIED  
OSHA PEL:200 PPM/STEL 300  
ACGIH TLV:200 PPM/STEL 300  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 106 G/L COMBINED PARTS A & B  
RTECS #:9999999VO

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)  
CAS:1317-65-3  
RTECS #:EV9580000  
Fraction by Wt: 20.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:MERCAPTAN TERMINATED POLYTHIOETHER (NON-HAZ)  
CAS:119147-78-3  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM HYDROXIDE (NON-HAZ)  
CAS:216  
45-51-2  
RTECS #:BD0940000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:MAGNESIUM OXIDE (NON-HAZ)  
CAS:1309-48-4  
RTECS #:OM3850000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 PARTICULATE  
ACGIH TLV:10 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: BURN, TEAR, RED, POSSIBLE  
TRANSIENT CORNEAL CLOUDING. SKIN: BU

RN, DRYING, CRACKING.

INHALATION: COUGH, CHEST PAIN, THROAT IRRIT, HEADACHE, DIZZY,  
ANESTHETIC, CNS EFFECTS, REVERSIBLE LIVER DAMAGE . INGEST: DROWSY,  
DIZZY, NAUSEA.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH LUKEWARM WATER FOR 15 MINUTES. IF SYMPTOMS  
PERSIST, CONSULT PHYSICAN. SKIN: WASH THOROUGHLY WITH SOAP AND  
WATER. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE  
TO FRESH AIR. IF SYMPTOMS ARE PRESENT  
CONSULT A PHYSICIAN. INGEST:  
DO NOT INDUCE VOMIT.

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC

Flash Point:25.0F,-3.9C

Lower Limits:1.8

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER.

Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL  
HEAT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE  
BUILDUP IN CLOSED CONTAINERS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. WEAR AIR-SUPPLIED  
RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBENT.  
SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH SUITABLE SOLVENT.

=====  
Handling and Storage  
=====

Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DONT CUT,  
PUNCTURE, WELD ON/NEAR DRUM. VAPORS ARE HEAVIER THAN AIR, MAY  
COLLECT IN LOW/CONFINED AREA.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:WHEN SPRAYING, APPLYING IN ANY CIRCUMSTANCES  
LIKELY TO PRODUCE AIRBORNE LEVELS IN EXCESS OF PEL, USE AN ORGANIC  
VAPOR CARTRIDGE RESPIRATOR OR AIR SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPOR BELOW PEL.

Protective Gloves:SOLVENT RESISTANT GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING, BEFORE SMOKING,  
EATING. AVOID INGESTION.

Supp

lemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NONE  
Vapor Density:>AIR  
Spec Gravity:1.329  
Evaporation Rate & Reference:NOT AVAILABLE  
Appearance and Odor:WHITE PASTE  
Percent Volatiles by Volume:19.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Hazardous Decomposition Products:OXIDES OF CARBON, SO2, TRACES OF H2S

===== Disposal Considerations =====

Waste Disposal Methods:EPA WASTE NO. D-001 AND D-035. DISPOSE OF SPILL  
IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any  
person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.