

EASTMAN KODAK COMPANY -- 103 8660 PRE-BLEACH & REPLENISH,PROCESS E-6  
AR,CONCENTRATE -- 6750-01-341-6134

===== Product Identification =====

Product ID:103 8660 PRE-BLEACH & REPLENISH,PROCESS E-6 AR,CONCENTRATE

MSDS Date:07/31/1996

FSC:6750

NIIN:01-341-6134

MSDS Number: CDJTT

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Coun

try:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Co

Composition/Information on Ingredients =====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 80 - 85%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:STABILIZING AGENT  
Fraction by Wt: 10 - 15%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE  
CAS:10117-38-1  
RTECS #:WT3530000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (CERCLA)  
CAS:60-00-4  
RTECS #:  
AH4025000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)  
CAS:67-56-1  
RTECS #:PC1400000  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:S, 200 PPM  
ACGIH TLV:S,200PPM/250STEL; 96  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:1-THIOGLYCEROL  
CAS:96-27-5  
RTECS #:TY8140000  
Fraction by Wt: 212F,>100C  
Vapor Pres:18 @ 68F  
Vapor Density:0.6  
Spec Gravity:1.20  
pH:6.1  
Solubili

ty in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID - ODORLESS

Percent Volatiles by Volume:80- 85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,  
SULFUR DIOXIDE, FORMALDEHYDE

===== Disposal Considerations =====

Waste Disposal Methods:DISCH

ARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT

TO FEDERAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT  
OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek compete  
nt professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.