Product ID:DEXTER EPOXY PATCH KIT 0151 CLEAR RESIN, 900660622 MSDS Date:05/18/1993 FSC:8040 NIIN:01-091-9671 Kit Part:Y MSDS Number: CDKKJ === Responsible Party === Company Name:AT&T Address:ONE OAK WAY **City:BERKELEY HEIGHTS** State:NJ ZIP:07922-2727 Country:US Info Phone Num:908-204-82 43 Emergency Phone Num:800-424-9300(CHEMTREC) CAGE:ATTEL === Contractor Identification === Company Name: AT AND T NETWORK SYSTEMS Address:1 OAK WAY Box:City:BERKLEY HEIGHTS State:NJ ZIP:07922 Country:US CAGE:0PWA9 Company Name:AT&T Address:ONE OAK WAY Box:City:BERKELEY HEIGHTS State:NJ ZIP:07922-2727 Country:US Phone:908-204-8243 CAGE:ATTEL

Ingred Name:PROPANE, 1-BUTOXY-2, 3-EPOXY-; (N-BUTYL GLYCIDYL ETHER) (BGE). (MFR'S I NVALID CAS #2426-80-6) CAS:2426-08-6 RTECS #:TX4200000 **OSHA PEL:50 PPM** ACGIH TLV:25 PPM Ingred Name: SILICA GEL; (SILICA, AMORPHOUS) CAS:112945-52-5 RTECS #:VV7310000 OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3 LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: IRRITATING TO SKIN AND EYES. CHRONIC: EXPOSURE MAY CAUSE SKIN SENSITIZATION. THE TOXICOLOGICAL PROPERTIES OF THIS PRODUCT MAY NOT BE FULLY INVESTIGATED. Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:EYES:FLUSH W/WARM WATER FOR AT LEAST 15 MINUTES. SEE MD. SKIN: FLUSH W/PLENTY OF WATER. WASH THOROUGHLY W/SOAP & WATER. HAND С LEANER OR RUBBING ALCOHOL. DO NOT USE OTHER SOLVENTS TO REMOVE MATERIAL FRO M SKIN. IF IRRITATION PERSISTS SEE MD. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. INHAL:REMOVE TO FRESH AIR. INGEST: OBTAIN MEDICAL ATTENTION.

Flash Point:200F,93C Lower Limits:0.4% Upper Limits:1.3% Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHERS, WATER SPRAY OR FOG, & FOAM. Fire Fighting Procedures:USE NIOSH APP

ROVED SCBA & FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:DENSE SMOKE & TOXIC GASES MAY BE PRODUCED UPON COMBUSTION.
======================================
Spill Release Procedures:SCRAPE UP & TRANSFER TO METAL CONTAINER FOR DISPOSAL. USE A RAG OR PAPER TOWEL W/DETERGENT TO WIPE & CLEAN OFF REMAINING RESIDUE. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
 Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. DO NOT MIX IN BATCHES OF GREATER THAN ONE POUND TOTAL. FOLLOW RECOMMENDED CURING PROCEDURES. Other Precautions:SILICA PARTICLES IN THIS PRODUCT ARE IN WETTED MATERIAL SO AIRBORNE EXPOSURE WILL NOT OCCUR UNLESS CURED MATERIAL IS SUBSEQUENTLY GROUND, MACHINED OR SANDED. IRRITANT, SENSITIZER. SLIGHTLY COMBUSTIBLE .
======================================
Respiratory Protection:NIOSH APPROVED RESPI RATOR APPROPRIATE FOR EXPOSURE OF CONCERN . NOT REQUIRED IF VENTILATION IS SUFFICIENT. Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED. GENERAL VENTILATION MAY BE ACCEPTABLE. Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER GLOVES. Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS . Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . OTHER CLOTHING &/OR EQUIPMENT AS (SUPP DATA) Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplem ental Safety and Health CNDTNS(POLYM):FAILURE TO OBSERVE CAUTIONS MAY RESULT IN EXCESSIVE HEAT BUILD-UP W/RELEASE OF TOXIC GASES. OTHER PROT EQUIP:NEEDED TO PROTECT SKIN & CLOTHING.
======================================

Boiling Pt:B.P. Text:284F,140C Vapor Pres: