View NSN Online: https://aerobasegroup.com/nsn/8040-00-853-8913

SANFORD CORP -- RUBBER CEMENT THINNER -- 8040-00-853-8913

============ Product Identification ==============

Product ID:RUBBER CEMENT THINNER

MSDS Date:05/01/1992

FSC:8040

NIIN:00-853-8913

MSDS Number: CDNPR === Responsible Party ===

Company Name:SANFORD CORP Address:2740 WASHINGTON BLVD

City:BELLWOOD

State:IL

ZIP:60104-1940 Country:US

Info Phone Num:800-228-5635

Emergency Phone Num:800-228-5635

CAGE:86874

=== C

ontractor Identification ===

Company Name: HAMMETT J L CO

Address:1 HAMMETT PL

Box:859057

City:BRAINTREE

State:MA ZIP:02185

Country:US

Phone:617-848-1000

CAGE:27028

Company Name: SANFORD CORPORATION

Address:2740 WASHINGTON BLVD.

Box:City:BELLWOOD

State:IL ZIP:60104 Country:US

Phone: 1-800-323-0749

CAGE:86874

====== Composition/Information on Ingredients ========

Ingred Name: N-HEPTANE

CAS:142-82-5

RTECS #:MI7700000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:500 PPM ACGIH TLV:400 PPM/

500STEL;9596
============ Hazards Identification ============
LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY & GI TRACTS. ACUTE- MAY CAUSE EYE IRRITATION. REPEATED/PROLONGED SKIN CONTACT MAY CAUSE DEFATTING & ITCHING. HIGH VAPOR CONCENTRATIONS MAY PRODUCE RESPIRATORY IRRI TATION. INGES
TION MAY CAUSE VOMITING

ASPIRATION HAZARD, CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure: IRRITATION, HEADACHE, NAUSEA, SKIN DRYNESS, TEARING, BLURRED VISION, ITCHING

Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL HELP IF SYMP

TOMS PERSIST. INHALED: REMOVE TO FRESH

AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLD EYELIDS OPEN, SKIN:WASH WITH SOAP & WATER, ORAL:DO NOT INDUC E VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION. IF SPONTANEOUS VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION.

	Fire	Fighting	Measures	
--	------	----------	----------	--

Flash Point: 20.0F, -6.7C

Lower Limits:1.1

Extinguishing Media: USE FOAM, DRY CHEMICAL OR CARBON DIOXIDE. USE WAT **ER**


TO COOL FIRE-EXPOSED CONTAINERS.

Fire Fighting Procedures: DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

 Accidental Release Measures	
 7 TOURGETTAL INCIDAGE INCAGALES	

Spill Release Procedures:WEA



Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT, FLAMES, SPARKS, HOT SURFACES AND OTHER SOURC

ES OF IGNITION

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE MAY BE FORMED DURING COMBUSTION.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF IN AN APPROVED INCINERATOR OR CONTRACT WITH LICENSED CHEMICAL WASTE DISPOSAL SERVICE. DISCHARGE, TREATMENT OR DISPOSAL IS SUBJECT TO FEDERAL, STATE OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.