View NSN Online: https://aerobasegroup.com/nsn/8030-00-602-0039

MORTON SALT -- THIOKOL MC-275 BASE CLASS B-1/4-1/2-2-4-6 B-1/2 -- 8030-00-602-0039

============ Product Identification ==============

Product ID:THIOKOL MC-275 BASE CLASS B-1/4-1/2-2-4-6 B-1/2

MSDS Date:01/29/1993

FSC:8030

NIIN:00-602-0039

Kit Part:Y

MSDS Number: CDPHB
=== Responsible Party ===

Company Name: MORTON SALT Address: 7341 ANACONDA AVE.

City: GARDEN GROVE

State:CA ZIP:92641

Info Phone Num:714-373-2837

Em

ergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:KO151

=== Contractor Identification ===

Company Name: MORTON INTERNATIONAL AEROSPACE POLYMER SYSTEMS

Address:7341 ANACONDA AVENUE

Box:City:GARDEN GROVE

State:CA ZIP:92641 Country:US

Phone:714-373-2837

CAGE:0U317

Company Name: MORTON SALT Address: 100 N RIVERSIDE PLASA

Box:City:CHICAGO

State:IL

ZIP:60606-1597 Country:US

Phone:312-807-2000

CAGE:KO151

====== Composition/Information on Ingredients ========

Ingred Name: CALCIUM CARBONATE (LIM

ESTONE) CAS:471-34-1

RTECS #:FF9335000 Fraction by Wt: 30-60%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:10 MG/M3 TDUST

Ingred Name: SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7 RTECS #:VV7330000 Fraction by Wt: 0.33%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3

Ingred Name: FORMALDEHYDE (SARA 302/313

) (CERCLA) LD50 ORAL RAT 800MG/KG

LD50 ORAL MOUSE 42MG/KG LD50 MORE INFORMATION ON FILE

CAS:50-00-0

RTECS #:LP8925000

Fraction by Wt: 15 MIN. CALL DR. SKIN: REMOVE CONTAM

CLOTHES/SHOES, WASH BEFORE REUSE. WASH W/SOAP/WATER. CALL DR. INHAL: GET FRESH AIR. CALL DR IMMED. IF NOT BREATH GIVE ARTIF RESP PREFERABLY MOUTH -TO-MOUTH. INGEST: CALL DR. INDUCE VOMITING BY GIVING IPECAC & 2 GLASSES H2O, OR STICK FINGER DOWN THROAT. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS/DROWSY/

NO GAG REFLEX PERSON.

Flash Point Method:SCC Flash Point:>200F,>93C


Autoignition Temp: Autoignition Temp Text: NE

Lower Limits:NA Upper Limits:NA

Extinguishing Media: USE AGENTS APPROVED FOR CLASS A HAZARDOUS E.G.

HALOGENATED AGENTS, FOAM, STEAM OR WATER FOG.

Fire Fighting Procedures:FIREFIGHTERS AND OTHERS EXPOSED TO PROD OF COMBUSTION SHOULD BE EQUIPED WITH NIOSH APPROVED POSITIVE PRESSURE SCBA & FULL PROTECTIVE CL



Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:PHENOLICS, OXIDES OF SULFUR, SMOKE,
SOOT, TOXIC FUMES (E.G. CARBON DIOXIDE & CARBON MONOXIDE), HYDROGEN
SULFIDE

Waste Disposal Methods:IF DISCARDED IN ORIGINAL UNUSED FORM MANAGE AT AUTHORIZED FACILITY IN COMPLIANCE W/LOCAL/FEDERAL/STATE REGS. CONTACTING APPROPRIATE GOVERNMENT

/ENVIRONMENTAL AGENCIES FOR

FURTHER DISPOSAL GUIDANCE IS R EQUIRED. RECYCLE, TREAT, OR INCINERATE MATERIAL.

======= Disposal Considerations ============

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professi onal advice to verify and assume responsibility for the suitability of this information to their particular situation.

===== Stability and Reactivity Data ========