

EASTMAN KODAK COMPANY -- 180 5332 RP X-OMAT FIXER & REPLENISHER, WORKING SOLUTION
-- 6525-01-075-8325

===== Product Identification =====

Product ID:180 5332 RP X-OMAT FIXER & REPLENISHER, WORKING SOLUTION

MSDS Date:08/02/1995

FSC:6525

NIIN:01-075-8325

Kit Part:Y

MSDS Number: CDQMV

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:146

50

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====

=== Composition/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 80-85%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE
CAS:7783-18-8
RTECS #:XN6465000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM THIOSULFATE
CAS:7772-98-7
RTECS #:XN6476000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (CERCLA)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 1-5%
Other
REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BISULFITE (CERCLA)
CAS:10192-30-0
RTECS #:WT3595000
Fraction by Wt: 212F,>100C
Melt/Freeze Pt:M.P/F.P Text:NP
Decomp Temp:Decomp Text:NP
Vapor Pres:18 @20C
Vapor Density:0.6
Spec Gravity:1.097
pH:4-4.2
Viscosity:NP
Evaporation Rate & Reference:NP
Solubility in Water:COMPLETE.
Appearance and Odor:LIQUID, COLORLESS, SLIGHT AMMONIA ODOR.
Percent Volatiles by

Volume:81.5
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, BAES, SODIUM HYPOCHLORITE (BLEACH).CONTACT W/BASE LIBERATES FLAMMABLE MATL.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:AMMONIA, SULFUR DIOXIDE, NITROGEN OXIDES (NOX), CHLORAMINE. HAZ COMBUST PROD:NONE (NON-COMBUSTIBLE).

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO NATIONAL/STATE/LOCAL LAWS. FLUSH TO SEWER W/LG AMTS OF WATER. CHEM(S) SUBJ TO REPORTING REQMTS OF SEC 313 TITLE III SARA/40CFR372:NONE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.