

UNI-KEM INTERNATIONAL CORPORATION/MFR OXYCHEM -- CNS WOOD PRESERVATIVE, GREEN,
73-0002 -- 6850-01-420-3082

===== Product Identification =====

Product ID:CNS WOOD PRESERVATIVE, GREEN, 73-0002

MSDS Date:01/01/1989

FSC:6850

NIIN:01-420-3082

MSDS Number: CDQQH

=== Responsible Party ===

Company Name:UNI-KEM INTERNATIONAL CORPORATION/MFR OXYCHEM

Address:513 HICKORY AVENUE

City:NEW ORLEANS (FORMALLY HAR
AHAN)

State:LA

ZIP:70123

Country:US

Info Phone Num:504-738-1623/713-623-2246

Emergency Phone Num:504-738-1623/800-533-2246

CAGE:4S446

=== Contractor Identification ===

Company Name:UNI-KEM INTERNATIONAL

Address:1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA

ZIP:70001

Country:US

Phone:504-835-7600/FAX:504-835-7608

CAGE:4S446

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC/MINERAL
SPIRITS

CAS:64742-88-7

Fractio

n by Wt: 60.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:COM'L NAPHTHENATE @ 8% COPPER

Fraction by Wt: 30.3%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ALIPHATIC PETROLEUM SOLVENT/KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: 9.3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:VOLATILE ORGANIC CONTENT (LESS WATER) AS LISTED ON MSDS:
4.94 LBS/GAL.

RTECS #:999

9999VC

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE HEADACHE, NAUSEA, EYE/SKIN IRRITATION.

Explanation of Carcinogenicity:NONE OF THE COMPONENTS OF THIS PRODUCT ARE REPORTED CA

RCINOGENS.

Effects of Overexposure:MAY CAUSE HEADACHE, NAUSEA, EYE/SKIN IRRITATION.

Medical Cond Aggravated by Exposure:RESPIRATORY DIFFICULTIES OR PREEXISTING SKIN SENSITIZATION. REPEATED EXPOSURE TO EMITTED VAPORS MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT. PREEXISTING SKIN SENSITIZATION MAY BE AGGRAVATED.

=====
===== First Aid Measures =====

First Aid:IF IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL ATTENTION.

EYE:FLUSH W/WATER FOR 15

MIN. SKIN:WASH W/SOAP & WATER. REMOVE

CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. INHALED:REMOVE FROM EXPOSURE. A ID OR RESTORE BREATHING AS NEEDED. INGESTED:DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:104F,40C

Lower Limits:N/A.

Upper Limits:N/A.

Extinguishing Media:USE FOAM, DRY CHEMICAL, CARBON DIOXIDE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Fire Fight

ing Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS
WHEN EXPOSED TO HEAT PREVENTING PRESSURE BUILDUP. FIRE FIGHTERS
SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT,
SPARKS, OPEN FLAMES. CLOSED CONTAINERS MAY EXPLODE DUE TO PRESSURE
BUILDUP WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE SPILL AREA. VENTILATE. RECOVER FREE

LIQUID BY ADDITION OF INERT ABSORBENT. SWEEP UP & PLACE MATERIAL IN
SUITABLE DISPOSAL CONTAINER. WASH DOWN SPILL AREA W/COPIOUS
QUANTITIES OF WATER.

Neutralizing Agent:MFR GAVE NO INFORMATION OF MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE OUT OF SUN & AWAY FROM HEAT,
SPARKS, OPEN FLAME. KEEP CONTAINER CLOSED & UPRIGHT TO PREVENT
LEAKAGE. STORE BETWEEN 40 & 120 F ONLY.

Other Precautions:NONE

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR OR OPEN AREA USE MSHA/NIOSH APPROVED
MECHANICAL FILTER RESPIRATOR. INDOOR WHERE VENTILATION IS
INADEQUATE, USE MSHA/NIOSH APPROVED CHEMICAL/MECHANICAL RESPIRATORS
DESIGNED TO REMOVE BOTH PARTI CULATES & VAPOR.

Ventilation:VENTILATE ALL APPLICATION AREAS PER 29CFR1910.

Protective Gloves:RECOMMENDED IF SKIN CONTACT IS LIKELY.

Eye Protection:GOGGLES OR SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equi

pmment:BUITABLE BARRIER CREAMS, IMPERVIOUS CLOTHING

& BOOTS ARE RECOMMENDED TO REDUCE CONTACT & LIMIT CONTAMINATION.

Work Hygienic Practices:WASH HANDS W/SOAP & WATER BEFORE EATING OR
USING WASHROOM. SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE. *NOTE:MSDS APPEARS
TO HAVE HAD MFR NAME & ADDRESS REMOVED AND UNI-KEM SUBSTITUTED.*

===== Physical/Chemical Properties =====

HCC:F4

NRC/State Lic Nu

m:NONE

Boiling Pt:B.P. Text:300F,149C

Vapor Density:>1

Spec Gravity:7.09 LB/GAL

Evaporation Rate & Reference: