View NSN Online: https://aerobasegroup.com/nsn/6850-01-435-5655

Product ID:OS-120 MSDS Date:10/18/1996 FSC:6850 NIIN:01-435-5655 MSDS Number: CDQQQ === Responsible Party === Company Name: DOW CORNING CORPORATION Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48640 Country:US Info Phone Num:517-496-6000/8577 (TRANSPORT) Emergency Phone Num:517-496-5900/800-424-9300(CHEMTREC) CAGE:5D028 === Contractor Identification === Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028

Ingred Name:HEXAMETHYLDISILOXANE CAS:107-46-0 RTECS #:JM9237000 Fraction by Wt: 89% Other REC Limits:TWA 200 PPM (MFR)

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER CAS:107-98-2 RTECS #:UB7700000 Fraction by Wt: 1 1% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:100 PPM/150STEL;9596

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYE, SKIN, RESPIRATORY & GI TRACTS. ACUTE- EYE: MAY CAUSE DISCOMFORT. SKIN: REPEATED/PROLONGED CONTACT MAY CAUSE DEFATTING. INHALE:MAY CAUSE DROWSINESS. ORAL:SMALL AMOUNTS TRANSFERRED TO M OUTH BY FINGERS SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY INJURE SLIGHTLY & CAUSE DROWSINESS. CHRONIC- DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, HEADACHE, NAUSEA, SKIN DRYNESS, TEARING, BLURRED VISION, ITCHING, DERMATITIS, DISCOMFORT Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUS CEPTIBLE TO THE EFFECTS OF THIS PRODUCT. First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES, HOLD EYELIDS OPEN, SKIN: WASH WITH SOAP & WATER. ORAL: SEEK MEDICAL ATTENTION. Flash Point Method:CC Flash Point:=-4.C, 24.8F Autoignition Temp:=365. C, 689.F Lower Limits:1.3% Upper Limits:18.6% Extinguishing Media: USE DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL FOAM/WATER FOG FOR SMALL FIRE. USE ALCOHOL FOAM, WATER SPRAY FOR LARGE FIRE. Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAI

## NERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND OR VERMICULITE. TRANSFER TO DISPOSAL DRUMS USING NON-SPARKING TOOLS. P REVENT LIQUID FROM ENTERING SEWERS OR WATERWAYS.

Neutralizing Agent:NOT RELEVANT

========

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA, AWAY FROM HEAT, FLAMES, SPARKS, HOT SURFACES AND STRONG OXIDIZING AGENTS. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions: AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. KEEP OUT OF REACH OF CHILDREN. DO NOT INGEST.

Respiratory Protection:NONE REQUIRED WH ERE ADEQUATE VENTILATION CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGH, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR. Ventilation:USE EXPLOSION-PROOF VENTILATION EQUIPMENT TO CONTROL VAPOR CONCENTRATIONS.

Protective Gloves:NITRILE FOR REPEATED/PROLONGED CONTACT Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE LOCATED NEARBY. WEAR APPROPRIATE PROTECTIVE CLOTHING FOR RISK OF EXPOSURE.

Work Hyg

ienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

HCC:F2

NRC/State Lic Num:NOT RELEVANT Vapor Pres:44.6 @ 77F Vapor Density:>1 Spec Gravity:0.77 Viscosity:0.64 CST Appearance and Odor:COLORLESS LIQUID; ETHER-LIKE ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid

:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT, FLAMES, SPARKS, HOT SURFACES, OTHER IGNITION SOURCES Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,

SILICONE DIOXIDE AND FORMALDEHYDE MAY BE FORMED DURING COMBUSTION.

Waste Disposal Methods:DISPOSE OF IN AN APPROVED INCINERATOR OR CONTRACT WITH LICENSED CHEMICAL WASTE DISPOSAL SERVICE. DISCHARGE, TREATMENT OR DISPOSAL IS SUBJECT TO FEDERAL, STATE OR LOCAL LAWS.

EPA D001 (IGNITABLE). FOR MORE INFORMATION, CALL DOW AT

517-496-6315.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.