

GIBSON-HOMANS CO -- BLACK JACK FIBER PLASTIC ROOF CEMENT -- 5610-00-236-4952

=====
Product Identification
=====

Product ID:BLACK JACK FIBER PLASTIC ROOF CEMENT

MSDS Date:08/28/1991

FSC:5610

NIIN:00-236-4952

MSDS Number: CDVGW

=== Responsible Party ===

Company Name:GIBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

City:TWINSBURG

State:OH

ZIP:44087

Country:US

Info Phone Num:216-425-3255 OR 216-467

-8128

Emergency Phone Num:216-425-3255 OR 216-467-8128

CAGE:33394

=== Contractor Identification ===

Company Name:GIBSON-HOMANS CO

Address:1623 E EUCLID AVE

Box:City:DES MOINES

State:IA

ZIP:50316

Country:US

Phone:515-262-9396

CAGE:33394

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 10-30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC = 300 G/L

RTECS #:999999

9VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-SKIN: MAY CAUSE IRRITATION.
EYES: MAY CAUSE IRRITATIONBLURRED VISION. INHAL: EXCESSIVE
BREATHING OF HIGH VAPOR CONCENTRATIONS CAN CAUSE NASAL &
RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, POSSIBL E
UNCONSCIOUS
NESS, ASPHYXIATION. INGEST: CAN CAUSE GI IRRIT, NAUSEA,
VOMIT, DIARRHEA, CHEMICAL PNNEUMONITIS.
Medical Cond Aggravated by Exposure:PREEXISTING LUNG/SKIN DISORDERS

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP & WATER. EYES: FLUSH WITH LARGE AMOUNTS
OF WATER. INHAL: REMOVE FROM AFFECTED AREA. IF BREATHING IS
DIFFICULT, GIVE OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIF RESP.
INGEST: DONT INDUCE VOMIT. SEE A DOCTOR IMMEDIATEL
Y.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:105F,41C
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR A SELF CONTAINED BREATHING APPARATUS.
WATER MAY CAUSE FROTHING, APPLY CAUTIOUSLY.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE SP
ILL AREA. RECOVER FREE LIQUID. ADD
ABSORBENT TO SPILL AREA. REMOVE SOURCES OF IGNITION. VENTILATE AREA
IF NEEDED.
Neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM IGNIT SOURCES. USE ONLY
WITH ADEQUATE VENT. AVOID PROLONGED/REPEATED CONTACT W/SKIN.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV

IS EXCEEDED, USE NIOSH/MSHA APPROVED
BREATHING APPARATUS.

Ventilation: MAINTAIN EXPOSURE BELOW TLV LEVEL.

Protective Gloves: SOLVENT RESISTANT.

Eye Protection: CHEMICAL GOGGLES.

Other Protective Equipment: NA

Work Hygienic Practices: REMOVE CONTAMINATED CLOTHING. LAUNDRY BEFORE
REUSE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 300 TO 315F

Vapor Pres: 2MM

Vapor Density: >1

Spec Gravity: 1.1

pH: NA

Evaporation Rate &

Reference: