

GRIGGS PAINT -- TT-P-91D, TYPE 2 #10076 BROWN #700N60 -- 8010-00-597-8199

=====  
Product Identification  
=====

Product ID:TT-P-91D, TYPE 2 #10076 BROWN #700N60

MSDS Date:05/01/1995

FSC:8010

NIIN:00-597-8199

MSDS Number: CDVKW

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-42

4-9300 CHEMTREC

Preparer's Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL N-AMYL KETONE (SARA 313) VP = 2.1 @ 68F

CAS:110-43-0

RTECS #:MJ5075000

F

raction by Wt: 8.0%  
Other REC Limits:100PPM

Ingred Name:ALIPHATIC HYDROCARBONS, STODDARD TYPE (SARA 313) VP= 2.0 @ 68F  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 34.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES (SARA 313) VP = 15 @ 100F  
CAS:64742-89-8  
Fraction by Wt: 3.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM

Ingred Name:CHLORINATED RESIN SOLUTION  
Fraction by Wt: 5.0%  
Other REC Limits  
:NONE RECOMMENDED

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)  
VP = 70 @ 68F  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 2.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: DIRECT CON

TACT MAY CAUSE

IRRITATION. PROLONGED CONTACT MAY CAUSE SKIN IRRITATION. INHAL:  
HIGH VAPOR CONCENTRATIONS MAY LEAD TO LUNG CHANGES, NAUSEA,  
VOMITING, COUGH, PULMONARY IRRITATION, CNS DEPRESSION. INGEST:  
POSSIBLE GASTROINTESTINAL DISTURBANCES. ASPIRATION OF PRODUCT INTO  
LUNGS MAY CAUSE PNEUMONITIS.\*

Effects of Overexposure:\* PULMONARY EDEMA AND HEMORRAGE. EYES: POSSIBLE  
IRRITATION W/DIRECT CONTACT. SKIN: POSSIBLE IRRITATION &/OR  
DERMATITIS. MAY BE ABSORBED THROUGH SKIN

Medical Cond Aggravated by Exposure:PRE-EXISTING DISEASES IN OR HISTORY  
OF AILMENTS INVOLVING SKIN, CENTRAL NERVOUS SYSTEM, LIVER AND  
KIDNEY.

=====  
First Aid Measures  
=====

First Aid:EYES: IMMEDIATELY FLUSH W/LARGE AMOUNTS WATER 15 MINUTES.  
SEEK MED AID. SKIN: WASH THOROUGHLY W/SOAP & WATER. SEEK MED AID IF  
IRRITATION PERSISTS. INGEST: IMMEDIATELY SEEK MED AID. DO NOT  
INDUCE VOMITING. DO NOT ATTEMPT TO GIVE ANYTHING BYMOUTH TO  
UN  
CONSCIOUS PERSON.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC

Flash Point:24.0F,-4.4C

Autoignition Temp:Autoignition Temp Text:474F

Lower Limits:0.9

Upper Limits:7.9

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING  
PERSONNEL. WATER MAY BE INEFFECTIVE, MAY BE USED TO COOL  
CONTAINERS. IF WATER USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTA

INERS TIGHTLY CLOSED. ISOLATE

FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAME. CLOSED  
CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL  
SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH  
AREA W/WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA  
HAS BEEN DECLARED SAFE.

=====  
Handling and Storage  
=====

=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED & UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING VAPOR & SPRAY MIST, SKIN & EYE CONTACT.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENT DOES NOT MAINTAIN INHALATION EXPOSURES BELOW TLV (PEL), USE MSHA/NIOSH APPROVED UNITS. FOLLOW MANUFACTURERS' INSTRUCTIONS & WARNINGS. IF WITHIN OSHA PROTECTION FACTOR, AIR PURIFYING OV/FILTER MAY BE USED.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves:RUBBER GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSON HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

NK

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:172 TO 334F

Vapor Density:>AIR

Spec Gravity:1.1 (WATER=1)

VOC Grams/Liter:4.63

Viscosity:67-86 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:ESSENTIALLY NIL

Appearance and Odor:VISCOUS LIQUID WITH TYPICAL PAINT ODOR

Percent Volatiles by Volume:28.06

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

S

tability Condition to Avoid:FLAMES, SPARKS, SMOKING & HEAT  
Hazardous Decomposition Products:CARBON MONOXIDE & CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIAL ON SPILLS. DISPOSE  
IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.