

RED DEVIL INC -- VINYL SPACKLING COMPOUND -- 5610-00-926-4562

=====
Product Identification
=====

Product ID:VINYL SPACKLING COMPOUND

MSDS Date:07/27/1990

FSC:5610

NIIN:00-926-4562

MSDS Number: CDVND

=== Responsible Party ===

Company Name:RED DEVIL INC

Address:MID AMERICA INDUSTRIAL DISTRICT

City:PRYOR

State:OK

ZIP:74361

Country:US

Info Phone Num:800-424-9300 (CHEMTREC)

Emergency Phone Num:800-424

-9300 (CHEMTREC)

CAGE:23577

=== Contractor Identification ===

Company Name:RED DEVIL, INCORPORATED

Address:ONE WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74361

Country:US

Phone:918-825-5744

CAGE:23577

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 100.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA)

CAS

:107-21-1
RTECS #:KW2975000
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL MONOETHYL ETHER (SARA 313)
CAS:111-90-0
RTECS #:KK8750000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200PPM

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)
CAS:67-56-1
RTECS #:PC1400000
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of En
try: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION OF DUST GENERATED FROM
DRIED PRODUCT MAY CAUSE RESPIRATORY IRRIT. CONTACT CAUSES EYE
IRRIT. PROLONGED/REPEATED CONTACT MAY CAUSE MILD SKIN IRRIT.
Effects of Overexposure:NONE

=====
===== First Aid Measures =====

First Aid:EYE: IMMED FLUSH W/LARGE AMOUNTS WATER, HOLD EYELID OPEN, GET
MED AID IF IRRIT PERSISTS. S
KIN: WIPE MATERIAL FROM SKIN
W/CLOTH/PAPER TOWEL, WASH EXPOSED AREA W/SOAP & WATER, GET MED AID.
INHAL: GET FR ESH AIR, TREAT SYMPTOMS. INGEST: CALL POISON
CONTROL/DR IMMED.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:USE MEDIA SUITABLE FOR ADJACENT MATERIALS.
Fire Fighting Procedures:NO SPECIAL PROCEDURES REQUIRED.

=====
===== Accidental Release Measures =====

Spil

