View NSN Online: https://aerobasegroup.com/nsn/9150-01-411-9132

Product ID:OIL 15 MSDS Date:04/13/1993 FSC:9150 NIIN:01-411-9132 **MSDS Number: CDVYS** === Responsible Party === Company Name: TRANE/SERVICE FIRST Address:4500 MORRIS FIELD DR City:CHARLOTTE State:NC ZIP:28208 Country:US Info Phone Num:704-398-4600 Emergency Phone Num:704-398-4600 CAGE:4X241 === Contractor Identifica tion === Company Name: TRANE/SERVICE FIRST Address:4500 MORRIS FIELD DR Box:City:CHARLOTTE State:NC ZIP:28208-5837 Country:US Phone:704-398-4600 CAGE:4X241 Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (SEVERE) HEAVY NAPHTHENIC; (REFINED MINERAL OIL)

CAS:64742-52-5 RTECS #:PY8035000 OSHA PEL:N/K ACGIH TLV:N/K

LD50 LC50 Mixture:NONE SPEC

IFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: PROLONGED CONTACT MAY CAUSE MINOR SKIN IRRITATION. Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:INHAL:OBSERVE PEL CONC (AIR) OF 5 M G/M3 OF MINERAL OIL MIST (OSHA). REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE OXYGEN/ARTIFICIAL RESPIRATION) . EYE:FLUSH W/LG AMTS OF WATER FOR @ LST 15 MINS. IF REDNESS/IRRIT PERSISTS, CONT PHYS. SKIN:WASH W/SOAP & WATER, WASH CLTHG BEFORE REUSE, INGEST: CALL A PHYSICIAN. Flash Point Method:COC Flash Point:>300F.>149C Extinguishing Media: USE WATER FOG, DRY CHEM, CO*2, FOAM OR SAND/EARTH TO EXTINGUISH FIRE . WATER SPRAY IS UNSUITABLE EXTINGUISHING AGENT. Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. Spill Release Procedures: STOP LEAK AND DIKE UP LARGE SPILLS. USE INERT ABSORBENT MATERIAL SUCH AS EARTH, SAND OR VERMICULITE FOR CLEAN-UP. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. ======================== Handling and Stora Handling and Storage Precautions: STORE IN COOL, DRY PLACE. AVOID EXPOSURE TO HEAT AND FLAME. PROTECT AGAINST EYE AND SKIN CONTACT. Other Precautions: NONE SPECIFIED BY MANUFACTURER. Respiratory Protection: NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN. Ventilation:NOT APPLICABLE. Protective Gloves: OIL RESISTANT RUBBER GLOVES. Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES . 0

ther Protective Equipment: RUBBER APRON. ANSI APPRVD EYE WASH & DELUGE SHOWER . Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER. Boiling Pt:B.P. Text:>500F,>260C Vapor Pres:10 Spec Gravity:0.89 Evaporation Rate & amp; Reference: NEGLIGIBLE Solubility in Water: INSOLUBLE Appearance and Odor: CLEAR AMBER, VISCOUS LIQUID - PETROLEUM ODOR. Percent Volatiles by V olume:NEGLIG Stability Indicator/Materials to Avoid:YES

 KEEP AWAY FROM STRONG OXIDIZING AGENTS SUCH AS CHROMIC ACID, HYDROGEN PEROXIDE AND BROMINE.
Stability Condition to Avoid:KEEP AWAY FROM STRONG OXIDIZING AGENTS SUCH AS CHROMIC ACID, HYDROGEN PEROXIDE AND BROMINE.
Hazardous Decomposition Products:UPON COMBUSTION CO*2 AND CO ARE GENERATED.

Was

te Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GOVERNMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice t o verify and

assume responsibility for the suitability of this information to their particular situation.