

MAGNAFLUX DIV OF ILLINOIS TOOL WKS INC -- SPOTCHECK DEVELOPER SKD-S2, AEROSOL --
6850-01-333-4117

=====
Product Identification
=====

Product ID:SPOTCHECK DEVELOPER SKD-S2, AEROSOL

MSDS Date:05/03/1996

FSC:6850

NIIN:01-333-4117

Kit Part:Y

MSDS Number: CDXCN

=== Responsible Party ===

Company Name:MAGNAFLUX DIV OF ILLINOIS TOOL WKS INC

Address:3624 WEST LAKE AVENUE

City:GLENVIEW

State:IL

ZIP:60025

Country:US

Info Phone Num:847-657-5300 / 5338 (FAX)

Emergency Phone Num:847-657-5300/800-424-9300(CHEMTREC)

Preparer's Name:CHERI A ZELEZNIK

CAGE:KO362

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

Company Name:MAGNAFLUX DIV OF ILLINOIS TOOL WKS INC

Address:3624 WEST LAKE AVENUE

City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300 / 5338 (F

AX)

CAGE:KO362

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL; (2-PROPANOL (ISOPROPANOL)) (SARA 313)

LD50 (ORAL RAT): 3.6 G/KG

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 40-70%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL

Ingred Name:ACETONE; (2-PROPANONE (ACETONE)) (SARA 313) (CERCLA) LD50

(ORAL RAT): 6 G/KG

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 10-30%

OSHA PEL:1000 PPM

ACGIH TLV:750PPM/1000STEL

Qty:5000 LBS

Ingred Name:PROPANE, 2-METHYL-; (ISOBUTANE) (PROPELLANT)

CAS:75-28-5

RTECS #:TZ4300000

Fraction by Wt: 30%

OSHA PEL:1000 PPM (MFR)

ACGIH TLV:N/K

=====
===== Hazards Identification =====

LD50 LC50 Mixture:SEE INGREDIENTS.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SKIN: CAN IRRITATE BY REMOVING
NATURAL SKIN OILS ON LONG OR REPEATED EXPOSURES.

EYES: IRRITATING,

BUT DOES NOT DAMAGE EYE TISSUE. INHALATION: CAUSES DIZZINESS AND
NAUSEA. INGESTION: NOT SIGNIFI CANT IN SMALL (MOUTHFUL) AMOUNTS.

CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE.

=====
===== First Aid Measures =====

First Aid:SKIN: WASH OFF W/SOAP & WATER. USE SOOTHING LOTION. EYES:
RINSE CAREFULLY UNDER UPP

ER & LOWER EYELIDS USING PLENTY OF WATER

FOR AT LEAST 15 MIN. INHAL: REMOVE TO FRESH AIR IF DIZZY/NAUS.

INGEST: DO NO T INDUCE VOMIT. ACCIDENTAL INGEST OF SINGLE MOUTHFUL
NOT EXPECTED TO CAUSE SIGNIFICANT HARM. NOTE: IN ALL SEV CASES,
CONT MD IMMED. LOC TELEPHONE OPERATORS CAN FURNISH NUMBER OF
REGIONAL POIS CTL CTR.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:2F,-17C

Lower Limits:2%

Upper Limits:15%

Extinguishing

Media:CARBON DIOXIDE, FOAM, WATER.

Fire Fighting Procedures:WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . KEEP CONTAINERS COOL WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:AEROSOL CANS MAY BURST OVER 130F (54C) AND ADD TO EXISTING FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:TURN OFF OR REMOVE SOURCES OF IGNITION. MOP UP OR SWEEP UP WITH ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING VAPORS. AVOID EYE CONTACT. AVOID REPEATED OR PROLONGED SKIN CONTACT. STORE AWAY FROM HEAT SOURCE. DO NOT SPRAY AROUND ARCS OR FLAME.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH RESPIRATOR WITH FILTER IF SPRAYED IN ENCLOSED, UNVENTILATED SPACE.

Ventilation:USE WHERE VENTILATION WILL CARRY VAPORS AWAY FROM OCCUPIED AREAS.

Protective Gloves:NITRILE RUBBER GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .

Other Protective Equipment:EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

VP: 150 MM @ 100F (38C) (BULK); 65 PSI @ 75F (24C) (AEROSOL).

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:>132F,>56C

Vapor P

res:SUP DAT
Vapor Density:3
Spec Gravity:0.87
pH:NEUT
Evaporation Rate & Reference:0.4 OF ETHER
Solubility in Water:90
Appearance and Odor:WHITE LIQUID, ALCOHOL ODOR
Percent Volatiles by Volume:90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:WHEN BURNING, SOOT, OXIDES OF CARBON.

===== Disposal Considerations

=====

Waste Disposal Methods:SEND TO A LICENSED FACILITY FOR PROPER DISPOSAL.
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person
utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.