View NSN Online: https://aerobasegroup.com/nsn/8040-01-389-6930

Product ID:BR95 ADHESIVE, PART A MSDS Date:01/24/1994 FSC:8040 NIIN:01-389-6930 Kit Part:Y MSDS Number: CDXNL === Responsible Party === Company Name: CYTEC INDUSTRIES INC Address:5 GARRET MOUNTAIN PLAZA **City:WEST PATERSON** State:NJ ZIP:07424 Country:US Info Phone Num:201-357-3100 **Emergency Phone Num** :800-424-3100 CAGE:0V7G8 === Contractor Identification === Company Name: CYTEC INDUSTRIES INC Address: FIVE GARRET MOUNTAIN PLAZA Box:City:WEST PATERSON State:NJ ZIP:07424 Country:US Phone:800-652-6013 CAGE:0V7G8 Company Name: KAMAN AEROSPACE CORP Address:OLD WINDSOR ROAD Box:City:BLOOMFIELD State:CT ZIP:06002 Country:US Phone:203-242-4164 CAGE:84955

Ingred Name:ALUMINUM (SARA 313) CAS:7429-90-5 RTECS #:BD0330000 Fraction by Wt: 40.58% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 DUST ACGIH TLV:10 MG/M3 DUST; 9495

Ingred Name:SILICON DIOXIDE (AMORPHOUS) CAS:67762-90-7 Fraction by Wt: 2.9% Other REC Limits:NONE RECOMMENDED OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: FIBERGLASS (FIBROUS GLASS)

CAS:65997-17-3

Fraction by Wt: 7.12+1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 RESP DUST

ACGIH TLV:10 MG/M3 (5 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ALLERGIC SKIN REACTIONS OR PRIMARY SKIN IRRITATION MAY BE PRODUCED BY PROLONGED &/OR REPEATED SKIN CONTACT W/EPOSY RESINS. OVEREXPOSURE TO VAPOR DURING HEAT CURING MAY CAUSE IRRITATION OR INJURY OF TH E RESPIRATORY TRACT OR EYE IRRITATION.

Explanation of Carcinogenicity:MANUFACTURER GAVE NO INFORMATION ABOUT CARCINOGENICITY. HMIS FOUND NO LISTING & DOES NOT EXPECT IT TO BE CARCINOGENIC.

Effects of Overexposure:EYE, SKIN, RESPIRATORY IRRITATION

Medical Cond Aggravated by Exposure:MFR GAVE NO INFORMATION OF MSDS.

First Aid:IN CASE OF SKIN CONTACT IMMEDIATELY WAS AFFECTED AREAS W/SOAP & PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING & SHOES. GET IMMEDIATE MEDICAL ATTENTION. DESTROY OR THOROUGHLY CLEAN SHOES BEFORE REUSE. DO NOT REUSE CONTAMINATED CLOTHING W/O LAUNDERING. IN CASE OF EYE CONTACT, IMMEDIATELY IRRIGATE W/PLENTY OF WA TER FOR 15 MIN. Flash Point Method:CC Flash Point:>200F,>93C Autoignition Temp:Autoignition Temp Text:N/A. Lower Limits:N/A. Upper Limits:N/A. Extinguishing Media: USE WATER, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING. **Unusual Fire/Explosion Hazard:NONE** Spill Release Proce dures:WEAR SUITABLE PERSONAL PROTECTIVE CLOTHING CHOSEN TO PROTECT FROM APPROPRIATE EXPOSURE. COVER SPILL W/INERT ABSORBENT & SWEEP UP & PLACE IN A WASTE DISPOSAL CONTAINER. FLUSH AREAS W/WATER. Neutralizing Agent:MFR GAVE NO INFORMATION OF MSDS. Handling and Storage Precautions: AVOID PROLONGED &/OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. Other Precautions:NONE ======== Exposure Controls/P ersonal Protection =========

Respiratory Protection: IF PEL, USE NIOSH RESPIRATOR APPROVED FOR THE MATERIAL & LEVEL OF EXPOSURE. FOR CUTTING, SANDING, GRINDING CURED MATERIAL, RESPIRATOR FOR DUST EXPOSURE MAY BE NECESSA RY. Ventilation: USE LOCAL EXHAUST TO KEEP EXPOSURE 90F,32C.

Waste Disposal Methods:DISPOSAL MUST BE I/A/W APPLICABLE FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this inf

ormation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.