

GARDNER ASPHALT CORP. -- ASPHALT PETROLEUM -- 5610-00-171-4722
===== Product Identification =====

Product ID: ASPHALT PETROLEUM
MSDS Date: 03/21/1990
FSC: 5610
NIIN: 00-171-4722
MSDS Number: CDXQL
=== Responsible Party ===
Company Name: GARDNER ASPHALT CORP.
Box: 5449
City: TAMPA
State: FL
ZIP: 33575-5449
Country: US
Info Phone Num: 800-237-1155
Emergency Phone Num: 800-237-1155
CAGE: 0VZ30
=== Contractor Identification ===
Company Name: GARDNER ASPHALT CORP
Address: 4161 E 7TH AVENUE
Box: 5449
City: TAMPA
State: FL
ZIP: 33605
Country: US
Phone: 800-237-1155/813-248-2101
CAGE: 0VZ30

===== Composition/Information on Ingredients =====

Ingred Name: MINERAL SPIRITS
CAS: 64742-48-9
Other REC Limits: NONE RECOMMENDED
ACGIH TLV: 5 MG/M3

Ingred Name: ASPHALT (PETROLEUM)
CAS: 8052-42-4
RTECS #: CI9900000
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM

===== Hazards

Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: CNS DEPRESSION, DIZZINESS,
HEADACHE, INTOXICATION, UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:DERMATITIS, CNS DISORDER.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: WASH W/SOAP & WATER. INHALATION:
MOVE TO FRESH AIR. GIVE OXYG
EN IF NEEDED.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:110F,43C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER SPRAY.
Fire Fighting Procedures:USE WATER SPRAY TO COOL EXPOSED CONTAINERS.
DON'T USE WATER STREAM DIRECTLY ON PRODUCT. USE SCBA & FULL
PROTECTIVE CLOTHING.

===== Accidental Release Measures =====

Spill Release Procedures:NOTIFY EMERGENCY PERSONNE
L. DIKE/CONTAIN
W/ABSORBENT. DO NOT FLUSH TO SEWER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT. VENTILATE TO
MAINTAIN