View NSN Online: https://aerobasegroup.com/nsn/8040-00-262-9011

CLIFTON ADHESIVE INC. -- FA1076 ADHESIVE, RUBBER BASE, GENERAL PURPOSE 8040-00-262-9011

Product ID:FA1076 ADHESIVE, RUBBER BASE, GENERAL PURPOSE MSDS Date:03/09/1995 FSC:8040 NIIN:00-262-9011 MSDS Number: CDXRN === Responsible Party === Company Name: CLIFTON ADHESIVE INC. Address: BURGESS PLACE City:WAYNE State:NJ ZIP:07470 Country:US Emergency Phone Num:NONE K NOWN CAGE:79833 === Contractor Identification === Company Name: CLIFTON ADHESIVE INC Address:BURGESS PL Box:City:WAYNE State:NJ ZIP:07470 Country:US Phone:201-694-0845; 973-694-0845 CAGE:79833 Company Name:RALRUBE INC. Address:36977 FOX GLEN Box:City:FARMINGTON HILLS State:MI ZIP:48331 Country:US Phone:248-661-0260, FAX 248-661-3941 CAGE:6X798

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA) CAS:78-93-3 R TECS #:EL6475000 Fraction by Wt: 65.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM ACGIH TLV:200 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TETRAHYDROFURAN (CERCLA) CAS:109-99-9 RTECS #:LU5950000 Fraction by Wt: 4.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM ACGIH TLV:200 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 4.0% Other REC Limits:NONE RECOMMEND ED OSHA PEL:50 PPM ACGIH TLV:50 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ACRYLONITRILE BUTADIENE POLYMER CAS:9003-18-3 Other REC Limits:NONE RECOMMENDED

Ingred Name:TRADESECRET #1397250002-5004P Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: NAUSEA/NARCOSIS. CHRONIC: L

IVER/KIDNEY DAMAGE/NS DAMAGE. WEAKNESS IN HANDS/FEET. LIVER/KIDNEY ABNORMALITIES Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS, LIVER/KIDNEY INJURIES.
======================================
First Aid:SKIN: WASH W/SOAP & WATER. CALL DR. EYE: FLUSH ABUNDANTLY W/CLEAN WATER. CALL DR. INGESTION: DON'T INDUCE VOMITING. CALL DR. INHALATION: MOVE TO FRESH AIR OR GIVE OXYGEN. USE CPR IF NEEDED. CALL DR.
======================================
Measures ====================================
Flash Point Method:OC
Flash Point:4F,-16C Autoignition Temp:Autoignition Temp Text:610F
Lower Limits:1.4
Upper Limits:11.8
 Extinguishing Media:CO2, FOAM, DRY CHEMICAL. Fire Fighting Procedures:NIOSH/MSHA APPROVED SCBA. USE WATER SPRAY TO COOL FIRE-EXPOSED STRUCTURES/DISPERSE VAPORS. Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. MAY TRAVEL LONG DISTANCES TO IGNITION SOURCES & FLASH BACK.
======================================
======
Spill Release Procedures: ABSORB/SHOVEL INTO STEEL CONTAINER & COVER.
======================================
Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED. STORE IN APPROVED SOLVENT STORAGE AREA. KEEP AWAY FROM IGNIT SOURCES/OXIDIZING AGENTS. Other Precautions:NA
======================================
Respiratory Protection: USE NIOSH APPROVED ATMOSPHERE-SUPPLYING OR AIR-PURIFYING RESPIRATOR FOR O

HCC:F2 Boiling Pt:B.P. Text:132F,56C Vapor Pres:71.3 Vapor Density:2.55

Spec Gravity:0.867 VOC Grams/Liter:5.43 Appearance and Odor:LIGHT AMBER, SWEET PUNGENT ODOR

Stability Indicator/Materials to Avoid:YES NA Stability Condition to Avoid:HEAT.

Hazardous Decomposition Products:OXIDES OF CARBON, NITROGEN, ZINC, SULFUR, HYDROGEN CHLORIDE

Waste Disposal Methods: ACCORDING TO FEDERAL/STATE/LOCAL CHEMICAL/SOLVENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibili ty for the suitability of this information to their particular situation.