

EASTMAN KODAK COMPANY -- 844 6163 T-MAX RS DEVELOPER AND REPLENISHER,WORKING SOLUTION -- 6750-01-304-2888

=====  
===== Product Identification =====

Product ID:844 6163 T-MAX RS DEVELOPER AND REPLENISHER,WORKING SOLUTION

MSDS Date:02/11/1998

FSC:6750

NIIN:01-304-2888

MSDS Number: CFCWM

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====

Composition/Information on Ingredients =====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 80 - 89%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX  
CAS:63149-47-3  
Fraction by Wt: 10 - 19%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA)  
CAS:123-31-9  
RTECS #:MX3500000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3  
ACGIH TLV  
:2 MG/M3; 9596  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA)  
CAS:7631-90-5  
RTECS #:VZ2000000  
Fraction by Wt: < 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:DIETHYLENE GLYCOL  
CAS:111-46-6  
RTECS #:ID5950000  
Fraction by Wt: < 1%  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT

KNOWN.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, GI TRACT.

ACUTE- CAUSES EYE IRRITATION. PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION, ALLERGIC SKIN REACTION. EXPECTED TO BE A LOW HAZARD BY INHALATION. SULFUR DIOXIDE , FORMED IN CONTACT WITH STRONG ACID/HEAT, CAN IRRITATE RESPIRATORY TRACT. HARMFUL IF SWALLOWED. CHRONIC - UNKNOWN.

Explanation of Ca

rcinogenicity:NONE

Effects of Overexposure:IRRITATION

Medical Cond Aggravated by Exposure:SOME ASTHMATIC OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA

=====  
===== First Aid Measures =====

First Aid:CALL PHYSICIAN IF SYMPTOMS DEVELOP. EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:FLUSH WITH PLENTY OF WATER. INHALED:MOVE TO FRESH AIR. PROV

IDE CPR/OXYGEN IF

NEEDED. ORAL:O NLY INDUCE VOMITING AT INSTRUCTION OF PHYSICIAN. CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE FLUID OR INDUCE VOMITING IF PATIENT IS UNCONSCIOUS OR HAS CONVULSIONS.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. OTHERWISE, ABSORB SPILL WITH INERT MATERIAL SUCH AS VERMICULITE, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REM

OVE RESIDUAL CO NTAMINATION.

Neutralizing Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL PLACE, AWAY FROM STRONG OXIDIZING AGENTS. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. AVOID INHALATION OF VAPORS OR MISTS. KEEP OUT OF REACH OF CHILDREN. FOR LABORATORY USE ONLY. NOT FOR DRUG, FOOD/HOUSEHOLD USE. USE WITH ADEQUATE VENTILATION .

=====

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. A NIOSH-APPROVED FULL-FACE POSITIVE-PRESSURE AIR-SUPPLIED RESPIRATOR MUST BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE RELEASED OR HAVE BEEN RELEASED.

Ventilation:GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS (10 ROOM VOLUMES PER HOUR).

Protective Gloves:RUBBER FOR REPEATED/PROLONGED CONTACT

Eye Protection:SAFETY GLASSES WITH SIDE SHIELD/GOGGLES

Other Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 @ 68F

Vapor Density:0.6

Spec Gravity:1.04

pH:8.6

Solubility in Water:COMPLETE

Appearance

and Odor:COLORLESS LIQUID - AMINE ODOR  
Percent Volatiles by Volume:> 80

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,  
OXIDES OF NITROGEN, OXIDES OF SULFUR

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT  
TO FE

DERAL, STATE OR LOCAL REGULATIONS. FLUSH TO SEWER WITH LARGE  
AMOUNT OF WATER, IF ALLOWED. SINCE EMPTIED CONTAINERS RETAIN  
PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS  
EMPTIED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all  
liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.