

DOW CORNING CORP -- SILASTIC (R) E RTV SILICONE RUBBER BASE. -- 8030-00-142-9124
===== Product Identification =====

Product ID:SILASTIC (R) E RTV SILICONE RUBBER BASE.

MSDS Date:12/06/1994

FSC:8030

NIIN:00-142-9124

Kit Part:Y

MSDS Number: CFCZY

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

F

raction by Wt: 3.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:TRIMETHYLATED SILICA
CAS:68909-20-6
Fraction by Wt: 27.0%
Other REC Limits:5 MG/M3 CEILING

Ingred Name:DIMETHYLVINYLATED & TRIMETHYLATED SILICA
CAS:68988-89-6
Fraction by Wt: 8.0%
Other REC Limits:5 MG/M3 CEILING

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO
OSHA:NO
Health Hazards Acute and Chronic:EYE: TEMPORARY DISCOMFORT W/MILD
REDNESS & DRYNESS, SIMILAR TO WINDBURN. INGEST: DIGESTIVE
DISCOMFORT.

=====
===== First Aid Measures =====

First Aid:EYE: IMMED FLUSH W/WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:212F,100C
Autoignition Temp:Autoignition Temp Text:NE
Lower Limits:NE
Upper Limits:NE
Extinguishing Media:WATER, WATER FOG, CO2, DRY CHE
MICAL, FOAM.
Fire Fighting Procedures:SCBA & PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB. CONTAINERIZE. MOP W/SOLVENT, WASH
W/MILD CAUSTIC DETERGENT OR HIGH PRESSURE STEAM. NONSILICONES: USE
INDUSTRIAL CLEANING MATERIALS. LARGE SPILL: DIKE. USE PERSONAL
PROTECTIVE EQUIPMENT. NOTIFY AUTHORITIES IF REQUIRED.

=====
===== Handling and Storage =====

===

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.

Ventilation:GENERAL VENTILATION RECOMMENDED.

Eye Protection:SAFETY GLASSES.

Work Hygienic Practices:WASH AT MEALTIME & END OF SHIFT.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:NE

Vapor Density:NE

Spec G

Gravity:1.14

pH:NA

Viscosity:800 POISES

Solubility in Water:NONE

Appearance and Odor:WHITE VISCOUS LIQUID.

Percent Volatiles by Volume: