View NSN Online: https://aerobasegroup.com/nsn/8030-01-364-7359

Product ID: PRO-SEAL 700 (07001) ACCELERATOR MSDS Date:01/19/1994 FSC:8030 NIIN:01-364-7359 **MSDS Number: CFDHC** === Responsible Party === Company Name: COURTAULDS AEROSPACE, INC Address:5430 SAN FERNANDO RD. Box:1800 **City:GLENDALE** State:CA ZIP:91209 Country:US Info Phone Num:818-240-2 060 Emergency Phone Num:800-424-9300 (CHEMTREC) CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

Ingred Name:ALIPHATIC AMINE CAS:63512-71-0 Fraction by Wt: 5% Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)(VP = 44.0 MMHG) C AS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 35.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:400 PPM/STEL 500 ACGIH TLV:400 PPM/STEL 500

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA) (VP = 70.0 MMHG) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 55.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM/STEL 300 ACGIH TLV:200 PPM/STEL 300 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: POS IRRIT/BURNING/TEARING/REDDENING/TRANSIENT CORNEAL CLOUDING. SKIN: POS IRRIT/REDNESS/BURNING/DRYING/CRACKING W/PROLONGED EXPOSURE. INHAL: POS NOSE/THROAT IRRIT, ANESTHETIC/OTHER CNS EFFECTS. REVERSABLE LIVER DAMAGE POS @ HIGH DOSES. INGES: POS HEADACHE/DIZZINESS/MENTAL DEPRESSION/NAUSEA/VOMITING/NARCOSIS* Effects of Overexposure:POS COUGHING, CHEST PAINS, THROAT IRRITATION, HEADACHES, DIZZINESS. *ANESTHESIA/COMA/DROWSINESS.

First Aid:EYES: FLUSH W/LUKE WARM WATER 15 MINUTES. IF SYMPTOMS PERSIST CONSULT DR. SKIN: WASH W/SOAP & WATER. IF SYMPTOMS PERSIST CONSULT DR. INHALATION: GET FRESH AIR. GET MEDICAL AID. INGESTION: SEE DR.

Flash Point Method:PMCC Flash Point:30.0F,-1.1C Lower

Limits:1.8 Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures:USE AIR-SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT-EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE BUILD-UP IN CLOSED CONTAINERS.
======================================
Spill Release Procedures:REMOVE ALL IGNITION SOURCES. WEAR AIR-SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER W/ABSORBENT. SCOOP INTO CONTAINER S. CERCLA REQUIREMENT FOR MEK = 5000 LBS.
======================================
Other Precautions: EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT/PUNCTURE/WELD ON/NEAR DRUM.
======================================
Respiratory Protection: WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS >TLV, USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR. Ventilation: GENER
AL TO MAINTAIN VAPORS AIR Spec Gravity:0.83
Appearance and Odor:BROWN PASTE Percent Volatiles by Volume:90.1
======================================
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:OXIDES OF CARBON & NITROGEN.

Waste Disposal Methods:EPA #D-001 & D-035 HAZARDOUS WASTE. DISPOSE IN COMPLIANCE W/APPLICABLE LAWS.

Disclaimer (prov

ided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.