

EASTMAN KODAK COMPANY -- 848 1525 FUSER OIL -- 6850-01-259-7154

===== Product Identification =====

Product ID:848 1525 FUSER OIL

MSDS Date:01/15/1997

FSC:6850

NIIN:01-259-7154

MSDS Number: CFKHN

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-7

22-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on Ingredients =====

Ingred Name:POLY (DIMETHYLS

ILOXANE)
CAS:63148-62-9
RTECS #:JJ6484500
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE. ACUTE- EYE:NO
SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN:LOW
HAZARD FOR RECOMMENDED HANDLING. INHALE
:EXPECTED TO BE A LOW
HAZARD. ORAL:EXPECTED TO BE A LOW INGESTION HAZARD. CHRONIC-
UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:TRANSIENT EYE IRRITATION
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING EYE
PROBLEMS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH
AIR. EYES:ANY MATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT
IMMEDIATELY WITH WATER. SKIN:WASH WITH SOAP & WATER. ORAL:DRINK 1-2
GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY
MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point:>200F,>93C
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL.
USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION
PRODUCTS MAY BE FORMED.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL WITH INERT MATERIAL SUCH AS
VERMICULITE. PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE
THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION. PREVENT RUNOFF FROM
ENTERING DRAINS, SEWERS OR STREAMS.
Neutralizing Agent:NOT RELEVANT

=====
===== Han

Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. STORE AWAY FROM STRONG OXIDIZING AGENTS.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. AVOID EYE CONTACT. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES

SHOULD BE MATCHED TO CONDITIONS

Protective Gloves:LATEX FOR PROLONGED/REPEATED CONTACT

Eye Protection:SAFETY GLASSES/GOGGLES RECOMMENDED

Other Protective Equipment:EYE BATH, WASHING FACILITIES

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.

Supplemental Safety and Health

ECOLOGICAL INFORMATION: THIS MATERIAL HAS NOT BEEN TESTED FOR ENVIRONMENTAL EFFECTS.

===== Physical/Chemical

Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:5 @ 77F

Spec Gravity:0.98

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS LIQUID - SLIGHT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, FORMALDEHYDE, OXIDES OF SILICON

=

===== Disposal Considerations =====

Waste Disposal Methods: DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL REGULATIONS. INCINERATE OR LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.