View NSN Online: https://aerobasegroup.com/nsn/3439-00-204-3203

## AUFHAUSER BROTHERS CORP -- ALLOY 605,5796 -- 3439-00-204-3203

Product ID:ALLOY 605,5796 MSDS Date:05/01/1997 FSC:3439 NIIN:00-204-3203 **MSDS Number: CFKQN** === Responsible Party === Company Name: AUFHAUSER BROTHERS CORP Address:39 WEST MALL City:PLAINVIEW State:NY ZIP:11803-4209 Country:US Info Phone Num:516-694-8696 Emergency Phone Num:516-694-8696/800-645-9486 CA GE:59401 === Contractor Identification === Company Name: AUFHAUSER CORP Address:39 WEST MALL Box:City:PLAINVIEW State:NY ZIP:11803-4209 Country:US Phone:212-757-6824/FAX: 516-694-8690 CAGE:59401

Ingred Name:MANGANESE (SARA 313) CAS:7439-96-5 RTECS #:OO9275000 Fraction by Wt: 1 - 2% Other REC Limits:NONE RECOMMENDED OSHA PEL:C, 5 MG/M3 (FUME) ACGIH TLV:0.2 MG/M3; 9596

Ingred Name:SILICON CAS:7440-21-3 RTECS #:VW0400000 Fractio n by Wt: 1% MAX Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:CHROMIUM (SARA 313) (CERCLA) CAS:7440-47-3 RTECS #:GB4200000 Fraction by Wt: 19 - 21% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA 313) (CERCLA) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 9 - 11% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9596

Ingred Name:T UNGSTEN,AS W,SOLUBLE COMPOUNDS. CAS:7440-33-7 RTECS #:YO7175000 Fraction by Wt: 14 - 16% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOE ESTABLISHED ACGIH TLV:1 MG/M3/3 STEL; 9596

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Fraction by Wt: 3% MAX Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 (TDUST) ACGIH TLV:5 MG/M3 (OXIDE FUME)

Ingred Name:COBALT (SARA 313) CAS:7440-48-4 RTECS #:GF8750000 Fraction by Wt: BALANCE Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.02 MG LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT RELEVANT. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYES, SKIN, CNS, RESPIRATORY TRACT. ACUTE- INHALING FUMES CAN CAUSE IRRITATION, DIZZINESS, WATERY EYES, HEADACHE, NAUSEA, COUGHING, CHEST PAINS. ARC RAYS CAN INJURE EYES & BURN SKIN. ELE CTRIC SHOCK CAN KILL. IR RADIATION CAN INJURE EYES. INGESTION IS UNLIKELY. CHRONIC- MAY CAUSE LUNG DAMAGE, SIDEROSIS. Explanation of Carcinogenicity: CONTAINS CHROMIUM. Effects of Overexposure: IRRITATION, SKIN DERMATITIS OR ECZEMA, COUGH, WHEEZING AND SHORTNESS OF BREATH, DECREASED PULMONARY FUNCTION, HEADACHE, NAUSEA, VOMITING, WEAKNESS, CONVULSIONS, RESPIRATORY AND SKIN SENSITIZATION, BUR NS, FEVER Medical Cond Aggravated by Exposure: INDIVIDUALS WITH PRE-EXISTING DISEASES OF T HE EYE, SKIN, RESPIRATORY TRACT MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES. First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EMPLOY FIRST AID TECHNIQUE RECOMMENDED BY RED CROSS. IF BREATHING IS DIFFICULT, PROVIDE OXYGEN/CPR. FOR ELECTRIC SHOCK, DISCONNECT POWER. FOR ARC BURNS, APPL Y COLD, CLEAN COMPRESSES & CALL A PHYSICIAN. IF EYE

CONTACT, FLUSH WITH WATER FOR 15 MINUTES

. IF SKIN CONTACT, WASH

WITH SOAP & WATER. INGESTION UNLIKELY (WIRE).

Flash Point:NONE Lower Limits:NOT RELEVANT Upper Limits:NOT RELEVANT Extinguishing Media:TO EXTINGUISH METAL FIRE, USE DRY SAND, DRY GRAPHITE OR OTHER CLASS "D" FIRE EXTINGUISHING POWDER. Fire Fighting Procedures:TREAT AS A METALLIC FIRE. WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazar d:NONE

Spill Release Procedures:NOT RELEVANT Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN DRY PLACE AWAY FROM ACIDS.
KEEP OUT OF REACH OF CHILDREN.
Other Precautions:AVOID EYE OR SKIN CONTACT. AVOID BREATHING FUMES. USE
WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING AND
BEFORE EATING AND DRINKING. REMOVE CO

NTAMINATED CLOTHING. LAUNDER BEFORE REUSE.

Respiratory Protection:USE NIOSH APPROVED SUPPLIED AIR RESPIRATORY PROTECTION OR RESPIRABLE FUME RESPIRATOR WHEN WELDING, BRAZING OR SOLDERING IN CONFINED SPACE OR WHERE LOCAL EXHAUST VENTILATION DOES NOT KEEP EXPOSURE BELO W TLV.

Ventilation:LOCAL EXHAUST VENTILATION SHOULD BE USED TO CONTROL EXPOSURE TO AIRBORNE FUMES OR DUST WHENEVER POSSIBLE.

Protective Gloves:

WELDER'S (HEAT RESISTANT) WHEN WELDING

Eye Protection: WELDER'S GOGGLES WHEN WELDING

Other Protective Equipment: EYE WASH STATION, SAFETY SHOWER, APRON

(ALUMINIZED), EAR PROTECTION (TO AVOID EXCESSIVE NOISE)

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

HCC:N1 NRC/State Lic Num:NOT RELEVANT Viscosity:NOT RELEVANT Evaporation Rate & amp; Referenc e:NOT RELEVANT Solubility in Water:INSOLUBLE Appearance and Odor:WELDING ROD

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:NONE Hazardous Decomposition Products:WELDING FUMES (OXIDES OF METAL BEING WELD) & GASES SUCH AS OZONE, CARBON MONOXIDE, CARBON DIOXIDE

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SU RROUNDING

ENVIRONMENT. KEEP PERSONNEL AWAY. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE W ITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate a nd

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.