

FEL-PRO CHEMICAL PRODUCTS LP -- GASKET SEALANT -- 5330-00-479-2847

=====
Product Identification
=====

Product ID:GASKET SEALANT

MSDS Date:02/14/1995

FSC:5330

NIIN:00-479-2847

MSDS Number: CFKRC

=== Responsible Party ===

Company Name:FEL-PRO CHEMICAL PRODUCTS LP

Address:3412 W TOUHY AVE

City:CHICAGO

State:IL

ZIP:60645

Country:US

Info Phone Num:847-568-2377

Emergency Phone Num:847-568-2377/CHEMTREC

800-424-9300

Preparer's Name:CATHY GRIFFITH

CAGE:GO402

=== Contractor Identification ===

Company Name:FEL-PRO CHEMICAL PRODUCTS DIV OF FELT PRODUCTS

Address:7450 N MCCORMICK

Box:1205

City:SKOKIE

State:IL

ZIP:60076-8205

Country:US

Phone:303-289-5651

CAGE:GO402

Company Name:FEL-PRO CHEMICAL PRODUCTS LP

Address:3412 WEST TOUHY AVE

Box:City:LINCOLNWOOD

State:IL

ZIP:60645

Country:US

Phone:303-289-5651

CAGE:05VH4

Company Name:PHILLIPS GASKET INC

Box:UNKNOW

CAGE:41962

Company Name:RP DIR-SET-PHILLIPS

GASKET
Box:UNKNOW
CAGE:9S754

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 60%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM
ACGIH TLV:400 PPM/500STEL;9596

Ingred Name:TALC (CONTAINING ASBESTOS)- ENCAPSULATED TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:0.2 FIBER/CC,A1;9596

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYES-SEVERELY IRRITATING.
SKIN-MILD IRRITANT. PROLONGED CONTACT MAY CAUSE DE
FATTING.
INHALATION-MAY CAUSE INJURY TO THE LUNGS, LIVER, OR KIDNEYS.
INGESTION- MAY BE HARMFUL OR FATAL IF SWALLOWED . CHRONIC: MAY
CAUSE PERMANENT NEURAL INJURY. EMBRYOTOXIC/FETOTOXIC EFFECTS HAVE
BEEN OBSERVED.
Effects of Overexposure:EYES- SEVERE IRRITATION. SKIN- IRRITATION AND
REDNESS. INHALATION- MAY CAUSE HEADACHE, NAUSEA, AND VOMITING.
INGESTION- IRRITATING TO MOUTH, THROAT, AND STOMACH, WITH NAUSEA.
Medical Cond Aggravated by Exposure:PREEXISTING PULMONARY AN

D

DERMATOLOGICAL DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO HAZARDOUS COMPONENTS.

=====
First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE MILK OR WATER TO DRINK. SEEK IMMEDIATE MEDICAL ATTENTION.

=====
= Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:22.0F,-5.6C

Lower Limits:1.0

Upper Limits:11.5

Extinguishing Media:ALCOHOL FOAM, FOAM, DRY CHEMICAL, CARBON DIOXIDE.

Fire Fighting Procedures:USE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER TO COOL EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:WATER STREAM DIRECTED INTO FIRE MAY CAUSE FROTHING W/ SUBSEQUENT SPREAD OF FLAME. CLOSED CONTAINERS MAY R

UPTURE OR EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. DIKE OR CONTAIN SPILL. WEAR APPROPRIATE PROTECTIVE EQUIPMENT DURING CLEANUP. ABSORB WITH INERT MATERIAL, SUCH AS CLAY. SWEEP OR SHOVEL INTO LOOSELY-COVERED WASTE CONTAINER AND REMOVE TO APPROPRIATE WASTE AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions

:USE WITH ADEQUATE VENTILATION. FOLLOW

ALL MSDS/LABEL PRECAUTIONS. GROUND AND BOND CONTAINERS WHEN TRANSFERRING MATERIAL. KEEP AWAY FROM HEAT.

Other Precautions:KEEP CONTAINER CLOSED WITH NOT IN USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF NEEDED, USE NIOSH-APPROVED VAPOR CARTRIDGE RESPIRTOR IN ACCORDANCE WITH APPLICABLE HEALTH AND SAFETY REGULATIONS AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:LOCAL EXHAUST AS NEEDED TO

CONTROL VAPOR OR DUST LEVELS TO
BELOW LOWEST COMPONENT TLV.

Protective Gloves: BUTYL RUBBER GLOVES.

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: EYE WASH AND SAFETY SHOWER.

Work Hygienic Practices: FOLLOW GENERAL INDUSTRIAL SAFETY PRACTICES
DURING USE. DO NOT SMOKE OR EAT DURING USE. DO NOT REUSE EMPTY
CONTAINERS.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC: F3

Boiling Pt: B.P. Text: 175-210F

Vapor De

nsity: >AIR

Spec Gravity: 0.7905

Viscosity: LOW

Evaporation Rate & Reference: < BUTYL ACETATE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: RED LIQUID WITH A SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG LEWIS OR MINERAL ACIDS. STRONG BASES OR OXIDANTS.

Stability Condition to Avoid: EXTREME HEAT.

Hazardous Decomposition Products: OXIDES OF CARBON. AROMATIC AND
ALIPHATIC HYDROCARBONS.

=====

=== Disposal Considerations =====

Waste Disposal Methods: REVIEW ALL CURRENT FEDERAL, STATE, AND LOCAL
REGULATIONS REGARDING HEALTH AND DISPOSAL FOR APPROPRIATE DISPOSAL
PROCEDURES. INCINERATION PREFERRED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be acc

urate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.