View NSN Online: https://aerobasegroup.com/nsn/6850-01-331-3349

EXXON CHEMICAL AMERICAS -- ISOPARAFFINIC PETROLEUM SOLVENT -- 6850-01-331-3349

Product ID: ISOPARAFFINIC PETROLEUM SOLVENT MSDS Date:05/22/1991 FSC:6850 NIIN:01-331-3349 MSDS Number: CFKTJ === Responsible Party === Company Name: EXXON CHEMICAL AMERICAS Box:3272 **City:HOUSTON** State:TX ZIP:77253 Country:US Info Phone Num:713-870-6885 Emergency Phone Num:713-870-6000/ 800-424-9300(CHEMTREC) CAGE:72190 === Contractor Identification === Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC Address:2210 HACKBERRY LN Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:4N760 Company Name: EXXONMOBIL CHEMICAL CO, DIV OF EXXON MOBILCORP. Address:13501 KATY FWY Box:3272 City:HOUSTON State:TX ZIP:77253-3272 Country:US Phone:281-870-6000 / 800-726-2015 CAGE:72190

Ingred Name:HYD

ROTREATED MIDDLE PETROLEUM DISTILLATE CAS:64742-46-7 RTECS #:JN9379645 Fraction by Wt: NP Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE:SLIGHTLY IRRIT BUT DOESNT INJURE EYE TISSUE.SKIN:LOW ORDER OF TOXICITY.FREQU/PROL CONTACT MAY IRRIT & CAUSE DERM.INHAL:HIGH VAP/AEROSOL CONC(>APPROX 700PPM ATTAINABLE @ELEVATED TEMP)IRRIT EYE/RESP TRACT,MAY CAUSE HEAD,DIZZ,ANESTHESIA,DROWS,UNCONSC,OTHER CNS EFFECTS INCLUDING DEATH.INGEST:MIN TOXICITY.SM AMTS(SUPPL) Effects of Overexposure:SLIGHT EYE IRRIT, IRIT SKIN, DERM, IRRIT EYE/RESP TRACT, HEADACHE, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSC, OTHER CNS EFFECTS, DEATH.SMALL AMTS ASPIRATED INTO RESPIRATORY SYSTEM MAY CAUSE MILD TO S EVERE PULMONARY INJURY POSSIBL

Y PROGRESSING TO DEATH.

Medical Cond Aggravated by Exposure:SKIN CONTACT MAY AGGRAVATE EXISTING DERM CONDITION.

First Aid:EYE:FLUSH W/LG AMTS OF WATER TIL IRRIT SUBSIDES.IRRIT PERSIST GET MED ATTN.SKIN:FLUSH W/LG AMTS OF WATER;USE SOAP IF AVAIL.REMOVE GROSSLY CONTAM CLOTH INCLUDE SHOES.INHAL:USING PROPER RESP PROTECTION IMMED REMOVE AFFECTED VICTIM FRM EXPO.ADMINISTER ART RESP IF BREATH STOP.KEEP @REST.CAL

L FOR PROMPT MED ATTN.INGEST:DONT INDUCE VOMIT.KEEP @REST.GET PROMPT MED.

Flash Point Method:TCC Flash Point:239F,115C Autoignition Temp:Autoignition Temp Text:594F Lower Limits:0.6 Upper Limits:7.0 Extinguishing Media:USE FOAM,DRY CHEMICAL,OR WATER SPRAY TO EXTINGUISH FIRE. Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPO SURF/PROTECT PERSONNEL.ISOLATE "FUEL"SUPPLY FRM FIRE.AVOID SPRAYING WATER DIRE CTLY INTO STORAGE CNTNT DUE TO DANGER OF BOILOVE Unusual Fire/Explosion Hazard:LIQ CAN BURN UPON HEATING TO TEP @/>FLASHPT.MATL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE INCENDIARY ELECT DISCHARGE.

Spill Release Procedures:REMOVE IGN SOURCES.PREVENT ADDN MATL DISCHARGE W/O HAZ.SM_IMPLEMENT CLEANUP PROCEDURES.LG-IMPLEMENT CLEANUP PROCEDURES.KEEP PUBLIC AWAY,ADVISE AUTHORITIES.IF PROD SUBJ TO CERCLA REPOR

TING NOTIFY NAT R ESP CNTNR.PREVENT SEWRE/H2OCOUSE/LOW AREA(NEUTRA)

Neutralizing Agent:SPILL:ENTRY-CONTAIN

W/SAND/EARTH.RECOVER-PUMP/ABSORBENT.H2O-SKIM/ADSORBENT.

Handling and Storage Precautions:HEALTH STUDIES HAVE SHOWN THAT MANY PETRO HYDROCARBONS POSE POT HUMAN HEALTH RISK-MAY VARY FRM PERSON TO PERSON.PRECAUT-MIN LIQ/VAP MIST/FUME EXPO. Other Precautions:DONT MIX/STORE W/STRONG OXIDANTS(LIQ CHLORINE.CONC

OXY).EMPTY CNTNR RETAIN PROD RESIDUE(LIQ &/OR VAP)-CAN BE DANGEROUS.DONT PRESSURIZE,CUT,WELD,BRAZE,SOLDER,DRILL,GRIND,EXPO SUCH CNTNR TO HEAT/FLAME/S PARK/STAT ELECT/IGN SOURCES-MAY (SUPPLE)

Respiratory Protection:WHERE CONC IN AIR MAY EXCEED LIMITS GIVEN & ENGINEERING,WORK PRACTICE OR OTHER MEANS OF EXPOSURE REDUCTION ARE NOT ADEQUATE NIOSH/MSHA APPROVED RESPIRATORS MAY BE NECESSARY TO PREVENT OVEREXPO

BY INHA L.

Ventilation: USE OF MECHANICAL DILUTION VENTI RECOMMENDED WHENEVER PRODUCT IS USED IN CONFINED SPACE, HEATED > AMB TEMP, OR AGITATED.

Protective Gloves: CHEM RESISTANT GLOVES

Eye Protection:SAF GLASS W/SIDE SHIELD

Other Protective Equipment:LONG SLEEVES

Work Hygienic Practices: LAUNDER CONTAM CLOTH BEF REUSE. STORAGE

TEMP/PRESSURE/TEMP/VISCO:AMBT/ATM/AMBT/NOT AVAIL.

Supplemental Safety and Health

HEALTH: ASPIRATED INTO RESP SYS DURING INGEST/VOMIT MAY CAUSE MILD TO SEVERE PULM IN

JURY, POSSIBLY PROGRESSING TO DEATH.CHRONIC TOXICITY DATA AVAI UPON REQUEST. OTHER PRECAUT:EXPLO, CAUSE INJURY/DEATH.EM PTY DRM SHOULD BE COMPLETELY DRAIN PROPERLY BUNG PROMPTLY RETURNED TO DR RECONDITIONER/PROPERLY DISPO OF.

HCC:N1 Boiling Pt:B.P. Text:532F,278C Melt/Freeze Pt:M.P/F.P Text: