

LHB INDUSTRIES -- SO-SURE WHITE #37875

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 00-878-5761  
MSDS Date: 10/03/1995  
MSDS Num: CFNBN  
Product ID: SO-SURE WHITE #37875  
MFN: 05  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST LOUIS MO 63134  
Info P  
Phone Number: 314-522-3141  
Emergency Phone Number: 314-522-3141 800-424-9300(CHEMTREC)  
Preparer's Name: GREGORY M. MCGOWAN  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: ENAMEL  
Unit of Issue: PT  
UI Container Qty: 0

=====  
Ingredients  
=====

Cas: 64742-89-8  
RT

ECS #: SE7546500  
Name: VM & P NAPHTHA  
% Wt: 8.87  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 300 PPM  
ACGIH TLV: 300 PPM  
-----

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (SARA III)  
% Wt: 14.66  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 200 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

Cas: 67-64-1  
RTECS #: AL3150000  
Name: ACETONE (SARA 313)  
% Wt: 25.42  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1000 PPM  
ACGIH TLV:  
750 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS  
-----

Cas: 74-98-6  
RTECS #: TX2275000  
Name: PROPANE  
% Wt: 14.91  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 1000 PPM  
-----

Cas: 75-28-5  
RTECS #: TZ4300000  
Name: 2-METHYL PROPANE  
% Wt: 3.67  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 800 PPM  
-----

Cas: 106-97-8  
RTECS #: EJ4200000  
Name: N-BUTANE  
% Wt: 5.87  
Other REC Limits: NON

E SPECIFIED  
OSHA PEL: 800 PPM  
ACGIH TLV: 800 PPM  
-----

Cas: 1330-20-7  
RTECS #: ZE2100000  
Name: XYLENE (SARA 313)  
% Wt: 3.55  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 100 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

RTECS #: 9999999VO  
Name: VOC: 449 G/L  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: NOT ESTABLISHED  
-----

Cas: 100-41-4  
RTECS #: DA0700000  
Name: ETHYL BENZENE  
(SARA 313)  
% Wt: &lt;1.77  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 100 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
=====

Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: YES  
Carcinogenicity Inds - NTP: NO  
IARC: NO  
OSHA: NO  
Effects of Exposure: INHAL: HARMFUL/FATAL. CHRONIC: BRAIN/NERVOUS SYSTER  
DAMAGE, ANESTHETIC. IRRITATION OF SKI

N/REPRIATORY TRACT (NAUSEA, HEADACHE, VOMITING, LIGHT HEADEDNESS, STAGGERING GAIT & GIDDINESS). EYE: IRRITATION.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.

First Aid: SKIN: WASH W/SOAP/WATER, WASH CLOTHES BEFORE REUSE. EYES: FLUSH W/WATER 15 MIN, CALL DR/OPHTHALMOLOGIST IMMEDIATELY. INGEST: DON'T INDUCE VOMIT. GET IMMEDIATE MED AID. INHAL: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NEEDED. GET MED AID. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====

=====

### Handling and Disposal

=====

Spill Release Procedures: REMOVE IGNITION SOURCES AND VENT AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: IN ACCORDING WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. DISCARD IN TRASH PICK-UP. DO NOT PUT IN HOME TRASH COMPACTOR OR INCINERATE.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER PRESSURE.

DON'T STORE WHERE >120F. AVOID BREATHING SPRAY/MIST/VAPOR.

=====

### Fire and Explosion Hazard Information

=====

Flash Point Text: 21.0F, -6.1C

Autoignition Temp Text: 874F

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. DON'T SPREAD BURNING LIQUID W/WATER SPRAY.

Fire Fighting Procedures: WATER INEFFECTIVE. USE H2O TO COOL CONTAINERS. WEAR

SELF-CONTAINED BREATHING APPARATUS. USE SHIELDING TO PROTECT PERSONNEL FROM BURSTING/RUPTURE/VENTING.

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPS (>120F) CONTAINERS MAY VENT/RUPTURE/BURST.

=====

### Control Measures

=====

Respiratory Protection: USE NIOSH/MSHA APPROVED MASK.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL: ACCEPTABLE.

Protective

Gloves: YES  
Eye Protection: CHEMICAL SPLASH GOGGLES  
Other Protective Equipment: IMPERVIOUS CLOTHES. EYE WASH STATION.  
Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DONT EAT/DRINK/SMOKE WHILE USING PRODUCT.

=====  
Physical/Chemical Properties  
=====

B.P. Text: NA  
M.P/F.P Text: NA  
Decomp Text: NA  
Vapor Pres: 60.0  
Vapor Density: >1.5  
Spec Gravity: 1.007  
PH: NA  
Viscosity: NA  
Solubility in Water: INSOLUBLE  
Appearance and Odor: WHITE PAINT  
Corrosion Rate: NA

=====  
Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: EXTREME HEAT.  
Materials To Avoid: NA  
Hazardous Decomposition Products: CARBON MONOXIDE AND POSSIBLE HYDROGEN CHLORIDE.  
Hazardous Polymerization Indicator: NO

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====

Other Information

=====

Transportation Information

=====

Responsible Party Cage: 0FTT5  
Trans ID NO: 89718  
Product ID: SO-SURE WHITE #37875  
MSDS Prepared Date: 10/03/1995  
Review Date: 10/16/1997  
MFN: 5  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: PT  
Container QTY: 0

=====

=====

Detail DOT Information

=====

DOT PSN Code: DTJ  
Symbols: D  
DOT Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PROD  
UCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 2-13

=====

Detail IATA Information

=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass:

75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203

=====  
Detail AFI Information  
=====

AFI PSN Code: ALR  
AFI Symbols: \*  
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.  
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)  
AFI Hazard Class: 2.1  
AFI UN ID NUM: UN1950  
Special Provisions: P4  
Back Pack Reference: A6.3

=====  
HAZCOM Label  
=====

Product ID: SO-SURE WHITE #37875  
Cage: 0FTT5  
Company Name: LHB INDUSTRIES  
Street: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO  
Zipcode: 63134  
Health Emergency Phone: 314-522-3141 800-424-9300(CHEMTREC)  
Label Required IND: Y  
Date Of Label Review: 10/12/1999  
Status Code: A  
Origination Code: G  
Hazard And Precautions: INHAL: HARMFUL/FATAL. CHRONIC: BRAIN/NERVOUS SYSTER  
DAMAGE, ANESTHETIC. IRRITATION OF SKIN/REPRIATORY TRACT (NAUSEA,  
HEADACHE,VOMITING, LI  
GHT HEADEDNESS, STAGGERING GAIT & GIDDINESS). EYE:  
IRRITATION.

=====  
Disclaimer (provided with this information by the compiling agencies): This  
information is formulated for use by elements of the Department of Defense.  
The United States of America in no manner whatsoever expressly or implied  
warrants, states, or intends said information to have any application, use or  
viability by or to any person or persons outside the Department

of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.