

PRATTVILLE BUILDERS INC -- PRIMER EPOXY COATING #724701 -- 8010-01-193-0516

=====
Product Identification
=====

Product ID:PRIMER EPOXY COATING #724701

MSDS Date:10/31/1995

FSC:8010

NIIN:01-193-0516

Kit Part:Y

MSDS Number: CFNCP

=== Responsible Party ===

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

Info Phone Num:205-365-2396/214

5/312-455-2662NIGHT

Emergency Phone Num:205-365-2396/2145/312-455-2662NIGHT

Preparer's Name:W. A. ELLISON

CAGE:0EAH4

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

Phone:205-365-2396/2145/312-455-2662NIGHT

CAGE:0EAH4

=====
Composition/Information on Ingredients ==

=====

Ingred Name:ALIPHATIC AMINE ADDUCT
CAS:31326-29-1
Fraction by Wt: 25.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA) VP = 6 @ 20C
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 15.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM CEILING
ACGIH TLV:50 PPM/STEL 150
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER (VP = 11 @ 20C)
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 50.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/STEL 150
ACGIH TLV:100 PPM/STEL 150

Ingred Name:TOLUENE (SARA 313) (CERCLA) (VP = 22 @ 20C)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/STEL 150
ACGIH TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:DIETHYLENETRIAMINE (VP = 1 @ 20C)
CAS:111-40-0
RTECS #:IE1225000
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 PPM
ACGIH TLV:1 PPM

Ingred Name:2-METHOXY-1-PROPANOL
CAS:1589-47-

Fraction by Wt: 15 MINUTES, LIFT LIDS. GET

MED AID. SKIN: FLUSH W/LARGE AMOUNTS OF WATER. REMOVE CONTAM CLOTHES, CALL DR.

=====
Fire Fighting Measures
=====

Flash Point:40.0F,4.4C

Autoignition Temp:Autoignition Temp Text:572F

Lower Limits:1.4

Upper Limits:11.2

Extinguishing Media:CLASS B EXTINGUISHERS (CO2, DRY CHEMICAL, ALCOHOL FOAM) FOR FLAMMABLE LIQUID. POLYMER FOAM PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, USE H2O (FOG NOZZLES

PREFERRED) TO COOL FIRE EXPOSED CONTAINERS, PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY BE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MED AID.

=====
Accidental Release Measures
=====

Spill Release Procedures:EVAC AREA. ELIMINATE IGNITS. DIKE/ABSORB W/ INERT MATERIAL. TRANSFER TO COVERED METAL CONTAINER

W/NONSPARKING

TOOLS. DONT CONTAMINATE SEWER/STREAM/GROUNDWATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:DONT STORE >115F. CLOSE CONTAINER AFTER USE. KEEP AWAY FROM CHILDREN. DONT REUSE CONTAINER FOR ANY PURPOSE. GROUND/BOND TO RECEIVING CNTNR WHEN

Other Precautions:NK TRANSFERRING. DONT WELD/BRAZE/CUT ON EMPTY CONTAINER. DONT PRESSURE TO EMPTY.

=====
Exposure Controls/Personal Protection
=====

Res

piratory Protection:USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR.

WHEN SPRAYING USE MECHANICAL PREFILTER. IN CONFINED AREA USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:GENERAL DILUTION & LOCAL EXHAUST.

Protective Gloves:IMPERMEABLE.

Eye Protection:CHEMICAL SPLASH GOGGLES & FACE SHIELD.

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health
MORE INFORMATION ON FILE.

=====
Physical/Chemical Properties
=====

HC

C:F2
Boiling Pt:B.P. Text:231 TO 405F
Melt/Freeze Pt:M.P/F.P Text:-50F,-46C
Decomp Temp:Decomp Text:1832F,1000C
Vapor Pres:22.0
Vapor Density:>AIR.
Spec Gravity:1.0
pH:4-7

Evaporation Rate & Reference:115F) AND SOURCES
OF IGNITION.

Hazardous Decomposition Products:SMOKE, CARBON MONOXIDE & CARBON
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE & LOCAL
REGULATIONS. EPA #D-001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.