View NSN Online: https://aerobasegroup.com/nsn/8010-01-193-0517

PRATTVILLE BUILDERS INC -- PRIMER EPOXY COATING CORRINHIB, LEAD #724700

8010-01-193-0517

============= Product Identification =================

Product ID:PRIMER EPOXY COATING CORRINHIB, LEAD #724700

MSDS Date:03/11/1996

FSC:8010

NIIN:01-193-0517

Kit Part:Y

MSDS Number: CFNCQ === Responsible Party ===

Company Name: PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL ZIP:36067 Country:US

Info Phone Num:205-365-2396/2145/312-455-2662NIGHT

Emergency Phone Num: 205-365-2396/2145/312-455-2662NIGHT

Preparer's Name: W. A. ELLISON

CAGE:0EAH4

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name: PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL ZIP:36067 Country:US

Phone:205-365-2396/2145/312-455-2662NIGHT

CAGE:0EAH4

====== Compositio

n/Information on Ingredients =======

Ingred Name: TOLUENE (SARA 313) (CERCLA) (VP = 22 @ 20C

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 10.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM/STEL 150

ACGIH TLV:50 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 20.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER (VP = 11 @ 20C

CAS:107-98

-2

RTECS #:UB7700000 Fraction by Wt: 5.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/STEL 150

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)

(VP = 70 @ 20C)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 15.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM/STEL 300 ACGIH TLV:200 PPM/STEL 300

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TALC CAS:14807-96-6 RTECS #:MW2700000

Fraction by Wt: 15.0%

Other REC Limits: NONE RECO

MMENDED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3

Ingred Name: SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7 RTECS #:VV7330000

Fraction by Wt: 15 MINUTES, LIFT LIDS. GET

MED AID. SKIN: FLUSH W/LARGE AMOUNTS OF WATER. REMOVE CONTAM

CLOTHES, CALL DR.

========== Fire Fighting Measures ==============

Flash Point:24.0F,-4.4C

Autoignition Temp: Autoignition Temp Text: 572F

Lower Limits:1.4 Upper Limits:11.2

Extinguishing Media:CLASS B EXTINGUISHERS (CO2, DRY CHEMICAL, ALCOHOL FO

AM) FOR FLAMMABLE LIQUID. POLYMER FOAM PREFERRED FOR LARGE FIRES. Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE H2O (FOG NOZZLES PREFERRED) TO COOL FIRE EXPOSED CONTAINERS, PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY BE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MED AID.

========= Accidental Release Measures ============

Spill Re

lease Procedures:EVAC AREA. ELIMINATE IGNITS. DIKE/ABSORB
W/INERT MATERIAL. TRANSFER TO COVERED METAL CONTAINER W/NONSPARDING
TOOLS. DONT CONTAM SEWERS/STREAMS/GROUNDWATER.

============= Handling and Storage ==========================

Handling and Storage Precautions:DONT STORE >115F. CLOSE CONTAINER
AFTER USE. KEEP AWAY FROM CHILDREN. DONT REUSE CONTAINER FOR ANY
PURPOSE. GROUND/BOND TO RECEIVING CNTNR WHEN **
Other Precautions:** TRANSFERRING. DONT WELD/BRAISE/CUT ON EM

PTY

CONTAINER. DONT PRESSURE TO EMPTY.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: USE NIOSH CHEMICAL CARTRIDGE RESPIRATOR. FOR SPRAYING USE MECHANICAL PREFILTER. IN CONFINED AREA USE AIR SUPPLIED RESPIRATOR.

Ventilation:LOCAL EXHAUST.

Protective Gloves:IMPERMEABLE.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health

KEY1:F3. MORE INFORMATION ON FILE.

==== Physical/Chemical Properties =========

HCC:F2

Boiling Pt:B.P. Text:175 TO 248F

Melt/Freeze Pt:M.P/F.P Text:-50F18C

Decomp Temp:Decomp Text:1832F,1000C

Vapor Pres:70.0

Vapor Density:>AIR.

Spec Gravity:1.3

pH:4-7

Viscosity:63-73 KU

Evaporation Rate & Evaporation R

OF IGNITION.

Hazardous Decomposition Products: SMOKE, CARBON MONOXIDE & CARBON

DIOXIDE.

======= Disposal Considerations ============

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS. EPA #D-001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suita

bility of this information to their particular situation.