

DEL PAINT CORP. -- TT-E-2784 RED -- 8010-01-380-3288

===== Product Identification =====

Product ID:TT-E-2784 RED
MSDS Date:06/14/1995
FSC:8010
NIIN:01-380-3288
MSDS Number: CFNFL
=== Responsible Party ===
Company Name:DEL PAINT CORP.
Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Info Phone Num:405-672-1431/FAX 405-672-0804
Emergency Phone Num:800-424-9300 24 HRS
CAGE:JO954

=== Contractor Identification ===

Company Name:DEL PAINT CORP.
Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431/FAX 405-672-0804
CAGE:JO954
Company Name:DEL PAINT MFG
Address:3105 EAST RENO
Box:City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL
CAS:57-55-6
RTECS #:TY2000000
Fraction by Wt: 6.25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL MONOISOBUTYRATE

CAS:25265-77-4

Fraction by Wt: 4.86%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC

CAS:108-01-0

RTECS #:KK6125000

Fraction by Wt: 0.38%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE

CAS:123-96-6

RTECS #:RH0795000

Fraction by Wt: 0.18%

Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENTS

Fraction by Wt: 88.33%

Other REC Limits:NONE RECOMMENDED

Ingred Name

:VOC = 1.7 LBS/GL

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: HEADACHE, NAUSEA, IRRITATION.

EYE: IRRITATION. CHRONIC: SKIN: IRRITATION.

Medical Cond Aggravated by Exposure:LUNG DISEASE

=====
===== First Aid Measures =====

=====

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES. CALL DR.

SKIN: WASH W/SOAP & WATER. INGEST: GIVE 2 GLASSES OF WATER TO

DRINK. CALL DR.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>212F,>100C

Autoignition Temp:Autoignition Temp Text:216F

Lower Limits:NONE

Upper Limits:NA

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:USE SCBA (PRESSURE DEMAND NIOSH/MSHA APPROV

ED)

& FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL MAY SPLATTER ABOVE 212F. POLYMER FILM MAY BURN.

===== Accidental Release Measures =====

Spill Release Procedures:EVAC AREA. FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. DIKE/ABSORB. TRANSFER TO SEPARATE, SUITABLE CONTAINER FOR RECOVERY/DISPOSAL. DONT CONTAMINATE SEWERS, OPEN BODIES OF WATER.

===== Handling and Storage =====

Handling and Storage

Precautions:KEEP FROM FREEZING.

Other Precautions:KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR

Ventilation:NORMAL (FAN)

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:EYEWASH STATION

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F

Melt/Freeze Pt:M.P/

F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:350F,177C

Vapor Pres:NONE

Vapor Density:>AIR

Spec Gravity:1.01

pH: