## View NSN Online: https://aerobasegroup.com/nsn/5610-00-618-0258 CROSSFIELD PRODUCTS CORP -- DEX-O-TEX QUICK SET PASTE -- 5610-00-618-0258 Product ID:DEX-O-TEX QUICK SET PASTE MSDS Date:01/01/1992 FSC:5610 NIIN:00-618-0258 MSDS Number: CFQWM === Responsible Party === Company Name: CROSSFIELD PRODUCTS CORP Address:3000 E HARCOURT ST City:COMPTON State:CA ZIP:90221 Country:US Info Phone Num:310-886-9100 **Emergency Phone Num:310-8** 86-9100 CAGE:60782 === Contractor Identification === Company Name: CROSSFIELD PRODUCTS CORP. Address:3000 EAST HARCOURT ST.

Box:City:COMPTON

State:CA ZIP:90221 Country:US

Phone:310-886-9100

CAGE:60782

======= Composition/Information on Ingredients ========

Ingred Name: CARBOXYLATED SBR LATEX CAS:30174-67-5 OSHA PEL:N/K ACGIH TLV:N/K

========== Hazards Identification ===============

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:N

O Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:MAY CAUSE EYE AND SKIN IRRITATION. CHRONIC:NOT ESTABLISHED. Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:NOT ESTABLISHED.
======================================
First Aid:INHAL:MOVE SUBJECT TO FRESH AIR. EYES:FLUSH W/WATER FOR AT LEAST 15 MINUTES & CALL MD. SKIN:W ASH AFFECTED AREAS W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGEST:INDUCE VOMITING & CAL MD AT ONCE.
======================================
Flash Point:>212F,>100C Extinguishing Media:WATER, CO*2, DRY CHEMICAL. Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:NONE KNOWN.
======== Accidental Release Measures ==========
Spill Release Procedures:CLEAN UP W/WATER & ALLO W TO DRY. SODIUM OR CALCIUM CHLORIDE CAN BE SPRINKLED ON SPILL WHICH WILL COAGULATE LATEX, THEN FLUSH W/WATER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
============ Handling and Storage ==============
Handling and Storage Precautions:AVOID BREATHING SPRAY MISTS OR HEATED VAPORS. KEEP PRODUCT FROM FREEZING TO AVOID COAGULATION. Other Precautions:NONE SPECIFIED BY MANUFACTURER.
====== Exposure Controls/Personal Protection ========
Respirat

ory Protection: NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED - IF NOT, USE A NIOSH APPROVED RESPIRATOR. Ventilation: LOCAL EXHAUST & OR MECHANICAL (GENERAL) VENTILATION. Protective Gloves: CHEMICAL RESISTANT OR RUBBER GLOVES. Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS. Other Protective Equipment: ANSI APPROVED EYE WASH FOUNTAIN & DELUGE SHOWER. OTHER PROTECTIVE EQUIPMENT AS REQUIRED TO PREVENT SKIN CONTACT. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Sa fety and Health SPEC GRAV:1.01-1.02 (H\*2O=1). ========= Physical/Chemical Properties =========== Boiling Pt:B.P. Text:212F,100C Vapor Pres: AS WATER Vapor Density: AS WATER Spec Gravity: SUPP DATA Evaporation Rate & Department Reference: AS WATER Solubility in Water:DISPERSIBLE Appearance and Odor:MILKY WHITE LIQUID EMULSION W/SLIGHT STYRENE ODOR. Percent Volatiles by Volume:70 ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:Y ES Stability Condition to Avoid: NON-REACTIVE, MAY COAGULATE IF FROZEN AT 32F. ======= Disposal Considerations ============ LANDFILL I/A/W PROCEDURES USED W/LATEX PRODUCTS & W/LOCAL, STATE & FEDERAL REGULATIONS.

Waste Disposal Methods: MAY BE INCINERATED OR DISPOSED OF IN SANITARY

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Ameri

ca in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.